



PA-2240

Order No.: 0170800

PRODUCTINFOS

PA power amplifier

- 2 x 240 W
- Routing switch for parallel operation on both channels
- Switchable 400 Hz high-pass filter 6 dB/oct.
- Soft start
- Temperature-controlled fan
- LED indication for clip, protect, overtemperature and output level
- Mains operation or 24 V emergency power operation

TECHNICAL SPECIFICATIONS

PA-2240

Power rating	480 W
Power rating at 8 Ω	2 x 240 W
Power rating at 100 V	2 x 240 W
Output impedance	25 V/2.6 Ω , 44 V/8 Ω , 70 V/20 Ω , 100 V/42 Ω
Channels	2
Inputs	1.2 V, bal.
Frequency range	35-20,000 Hz
S/N ratio	> 100 dB(A)

PA-2240

THD	< 1%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	1,300 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 55 A
Admiss. ambient temp.	0-40 °C
Width	483 mm
Height	88 mm
Depth	374 mm
Rack units, RU	2
Weight	18 kg
Connections	2 x XLR / screw contacts (inputs) screw contacts (speakers)
Packing dimensions (W x H x L)	0.48 x 0.18 x 0.54 m
Gross weight	20.14 kg
Net weight	18.12 kg