


PA-4240

Order No.: 0170820

PRODUCTINFOS

PA power amplifier

- 4 x 240 W
- Routing switches for parallel operation on 2 channels each
- Temperature-controlled fan
- Connection for external on/off switch
- LED indication for clip, protect, overtemperature and output level
- Mains operation or 24 V emergency power operation

TECHNICAL SPECIFICATIONS

PA-4240	
Power rating	960 W
Power rating at 4 Ω	4 x 240 W
Power rating at 100 V	4 x 240 W
Output impedance	31 V/4 Ω, 50 V/10.4 Ω, 70 V/20 Ω, 100 V/42 Ω
Channels	4
Inputs	1.2 V, bal.

PA-4240

Frequency range	55-17,000 Hz
S/N ratio	> 90 dB(A)
THD	< 1%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	2,720 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 113 A
Admiss. ambient temp.	0-40 °C
Width	483 mm
Height	133 mm
Depth	370 mm
Rack units, RU	3
Weight	28 kg
Connections	4 x XLR (inputs), screw contacts (speakers)
Packing dimensions (W x H x L)	0.55 x 0.21 x 0.49 m
Gross weight	30.54 kg
Net weight	28.62 kg