

PA-6600

Order No.: 0172390

PRODUCTINFOS

6-zone mono PA mixing amplifier

- 1 x 600 W
- 6 zones, can be controlled individually
- Chime, continuous sound and wailing sound, automatic mute, 2-tone chime or 4-tone chime (selectable)
- Bass, treble and master controls, level display via LEDs, regulated fan
- Insertions for various functions are available at option
- 17 V phantom power for electret microphones
- Connection for zone paging microphone PA-6000RC
- 1 insertion compartment at the front for automatic alarm message insertion PA-1120DMT, a tuner insertion or a CD player insertion, all available at option
- 3 insertion facilities on the rear panel for optional modules with the following features:

- PA-6FD: fault detection
- PA-6FM: fault monitoring
- PA-6FR: anti-feedback

- Mains operation and 24 V emergency power operation
- Removable mounting brackets

TECHNICAL SPECIFICATIONS

PA-6600

Peak output power	850 W
Power rating	600 W
Channels	5
Zones	6
Inputs	2.5 mV/5 kΩ, 0.3 V/5 kΩ (mic/line), 0.3 V/15 kΩ (line), 0.775 V/10 kΩ (preamplifier)
Frequency range	55-16,000 Hz
Equalizer bass	± 10 dB/100 Hz
Equalizer treble	± 10 dB/10 kHz
S/N ratio	> 70 dBA (mic), > 80 dBA (line)
THD	< 1%
Phantom power	17 V
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	1,700 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 50 A
Admiss. ambient temp.	0-40 °C
Width	430 mm
Height	133 mm
Depth	352 mm
Rack units, RU	3
Weight	20 kg
Connections	3 x combo 6.3 mm/XLR (mic/line), 2 x RCA L/R (line), 1 x 6.3 mm jack (preamplifier), 1 x RJ45 (push-to-talk mic), screw contacts (telephone system), 1 x 6.3 mm jack (ext. amplifier), 1 x RCA L/R (record), screw contacts (speakers)
Packing dimensions (W x H x L)	0.55 x 0.22 x 0.48 m
Gross weight	23.58 kg
Net weight	21.56 kg