



## ATS-20R

Order No.: 0255640

### PRODUCTINFOS

#### 16-channel Digital Voice Transmission System, 863-865 MHz

- Suitable as a tour guide system and for any other application in which a certain voice source is to be distributed to one or more receivers
- High resistance to interference due to digital transmission
- High operating range
- Frequency range perfectly adapted to voice transmissions
- Parallel operation of up to 4 different channels possible without any interference
- Extra small and lightweight transmitters and receivers
- Licence-free in the EU

#### 16-channel miniature receiver

- Supplied with matching clip-on earphone
- Switches off automatically after not receiving an input signal for 20 minutes (power-saving function)
- LCD for indicating channel, carrier signal, volume and battery status
- Autolock function
- Lanyard
- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)

- Micro USB charging connection for ATS-12CB, ATS-35CB or USB charger, available at option
- Dimensions: 40 x 87 x 12 mm
- Weight: 37 g

**Licence-free in the EU.**

## TECHNICAL SPECIFICATIONS

### ATS-20R

#### General information

Description	16-channel digital miniature receiver
Carrier frequency range	863-865 MHz
Admiss. ambient temp.	0-40 °C

#### Specifications receiver

Power supply receiver	integrated rech. lithium batt. (3.7 V/600 mAh)
Width receiver	40 mm
Height receiver	87 mm
Depth receiver	12 mm
Weight receiver	37 g
Connections receiver	3.5 mm jack (earphone), micro USB charging port