



ATS-20T

Order No.: 0255650

PRODUCTINFOS

16-channel Digital Voice Transmission System, 863-865 MHz

- Suitable as a tour guide system and for any other application in which a certain voice source is to be distributed to one or more receivers
- High resistance to interference due to digital transmission
- High operating range
- Frequency range perfectly adapted to voice transmissions
- Parallel operation of up to 4 different channels possible without any interference
- Extra small and lightweight transmitters and receivers
- Licence-free in the EU

16-channel miniature transmitter,

for microphone operation and audio line signals.

- Supplied with electret tie clip microphone
- Microphone input/audio line input via 3.5 mm jack with automatic detection, depending on the configuration (mono/stereo)
- LCD for indicating channel and battery status

- Mute button
- Lanyard
- Transmitting power: ≤ 10 mW (EIRP), operating range: approx. 100 m
- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)
- Micro USB charging connection for ATS-12CB, ATS-35CB or USB charger, available at option
- Connection cable 801TG with 3.5 mm plug is available at option for certain JTS headband microphones
- Dimensions: 40 x 80 x 12 mm
- Weight: 37 g

Licence-free in the EU.

TECHNICAL SPECIFICATIONS

ATS-20T

General information

Description	16-channel digital miniature transmitter
Carrier frequency range	863-865 MHz
Admiss. ambient temp.	0-40 °C

Specifications transmitter

Transmitting power	≤ 10 mW
Operating range	100 m
Power supply transmitter	integrated rech. lithium batt. (3.7 V/600 mAh)
Width transmitter	40 mm
Height transmitter	80 mm
Depth transmitter	12 mm
Weight transmitter	37 g
Connections transmitter	3.5 mm jack (microphone/line in), micro USB charging port