



DH-95NP

Order No.: 0234100

PRODUCTINFOS

Dynamic hand-held microphones

- Low impedance
- With push-to-talk button
- Particularly suitable for CB and PA
- Supplied with microphone holder
- 300-6,000 Hz, 2.5 mV/Pa/1 kHz, 500 Ω

DH-95N: helix connection cable with open cable ends

DH-95NP: helix connection cable with 6.3 mm stereo plug

Dynamic hand-held microphone

- Low impedance
- With push-to-talk button (PTT)
- Particularly suitable for CB and PA
- Supplied with microphone holder
- 300-6,000 Hz, 2.5 mV/Pa/1 kHz, 500 Ω

- Helix connection cable with 6.3 mm stereo plug

TECHNICAL SPECIFICATIONS

DH-95NP

Description	hand-held microphone
Transmission method	cable
System	dynamic
Audio frequency range	300-6,000 Hz
Nominal impedance	500 Ω
Sensitivity	2.5 mV/Pa
Admiss. ambient temp.	0-40 °C
Weight	165 g
Cable	helix connection cable
Connection	6.3 mm stereo plug
Packing dimensions (W x H x L)	0.085 x 0.05 x 0.14 m
Gross weight	0.193 kg
Net weight	0.165 kg