

HSE-300/SK - Page: 1



HSE-300/SK

Order No.: 0234080

PRODUCTINFOS

Professional headband microphone,

with cardioid polar pattern and a high-quality sound which is suitable for any vocal or speech application. Innovative design features ensure a maximum suppression of both the impact sound and structure-borne noise as well as an extra low acoustic feedback, very comfortable to wear. Beige version.

- Corrosion-resistant neckband, easy to clean
- Drip ring (protects cartridge from moisture)
- Unobtrusive and secure fit due to cable routing in neck area incl. strain relief and cable bending protection
- Stable positioning
- Microphone windshield
- External power supply, e.g. via phantom power supply adapter EMA-1 or EMA-300P
- Bare cable ends

With regard to acoustic feedback, these microphones allow a particularly convenient operation due to the cardioid characteristic.



TECHNICAL SPECIFICATIONS

н	SF-	30	0/S	K

Description	headband microphone	
Transmission method	cable	
Polar pattern	cardioid	
System	electret	
Audio frequency range	50-18,000 Hz	
Nominal impedance	2 kΩ	
Sensitivity	2.3 mV/Pa	
Max. sound pressure	120 dB	
Power supply	DC 1.5-9 V	
Admiss. ambient temp.	0-40 °C	
Weight	18 g (w/o cable and plug)	
Connection	open cable ends	
Packing dimensions (W x H x L)	0.175 x 0.07 x 0.22 m	
Gross weight	0.205 kg	
Net weight	0.03 kg	