



# PA-4040MPX

Order No.: 0173450

## PRODUCTINFOS

### 4-zone mixer,

for general multi-room PA applications.

- 4 zones with user-defined routing of all input channels
- 3 inputs microphone/line via comb. jacks
- 2 inputs line stereo via RCA jacks
- Each input channel with gain control, 2-way tone control and zone routing switch
- Microphone inputs with 15 V phantom power, to be activated as required
- Priority function for channel 1, switchable
- Independent paging input, can be routed to each zone
- 4 zone outputs, can be adjusted individually
- Connection for monitor speaker
- Level control via VU meters for zone and monitor
- Adjustable headphone output
- Mains operation or 24 V emergency power operation

## TECHNICAL SPECIFICATIONS

### PA-4040MPX

Channels

5

**PA-4040MPX**

Zones	4
Inputs	5 mV/4 k $\Omega$ , 100 mV/10 k $\Omega$ (mic/line), 100 mV/30 k $\Omega$ (line)
Frequency range	50-17,000 Hz
Equalizer bass	$\pm$ 10 dB/100 Hz
Equalizer treble	$\pm$ 10 dB/10 kHz
S/N ratio	> 65 dB (mic), > 75 dB (line)
THD	< 1%
Phantom power	15 V
Mains voltage	$\sim$ 230 V
Mains frequency	50 Hz
Power consumption, operation	20 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 600 mA
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	133 mm
Depth	220 mm
Rack units, RU	3
Weight	4.5 kg
Connections	3 x combo 6.3 mm/XLR (mic/line), 2 x RCA L/R (line), 4 x plug-in screw terminal (zones), screw contacts (monitor speakers), screw contacts (mix out), screw contacts (paging), screw contacts (priority)
Packing dimensions (W x H x L)	0.28 x 0.22 x 0.57 m
Gross weight	5.68 kg
Net weight	4.7 kg