



IT-32EN

Order No.: 0160020

PRODUCTINFOS

Weatherproof horn speakers,

with EN 54-24 certification.

- 100 V line technique
- IP66 tested
- Light grey ABS housing (self-extinguishing, complies with the standard UL 94V-0)
- Cable inlet via high-strength cable gland
- Integrated high-pass filter for optimising the sound and stability
- Supplied with mounting bracket

TECHNICAL SPECIFICATIONS

IT-32EN

Active/passive	passive
Transmission technology	100 V
Total power rating	30 W
Power rating (RMS)	30/15/7.5 W

IT-32EN

Frequency range	350-10,000 Hz
Number of speakers	1
SPL	110 dB/W/m
Radiation angle/beam angle	H: 110°/V: 55°
Radiation angle, horizontal	110°
Radiation angle, vertical	55°
Features	EN 54-24 certification
Housing material	ABS, UL 94V-0
Colour	light grey
Mounting device	mounting bracket
Protection class	IP66
Admiss. ambient temp.	-25 °C to +70 °C
Dimensions	180 x 120 x 230 mm
Width	180 mm
Height	120 mm
Depth	230 mm
Weight	2.1 kg
Other features	weatherproof
Packing dimensions (W x H x L)	0.18 x 0.28 x 0.185 m
Gross weight	2.3 kg
Net weight	2.12 kg