



PREAMP-1UP

Order No.: 0171350

PRODUCTINFOS

Flush-mounted preamplifier

- For connection of power amplifiers
- Fitted metal base plate
- Connections and level controls for line input and microphone input

Description of features:

Preamplifier for connecting a dynamic microphone with 6.3 mm plug and a line source (e.g. tuner, CD player or MP3 player) via RCA jacks. Suitable for residential premises, small training rooms, practices, etc. ...The volume of the sound sources can be adjusted separately. The PREAMP-1UP features an on/off switch. The preamplified signal can then be transmitted to several power amplifiers (low-voltage and/or 100 V amplifier). Installation is done in a standard flush-mounted socket with a depth of 63 mm. The scope of delivery includes an imprinted cover (50 x 50 mm). A respective adapter frame for the corresponding range of switches is available from electrical wholesalers.

TECHNICAL SPECIFICATIONS

PREAMP-1UP

Line input	400 mV (line)
	4 mV (mic)
Input control voltage	DC 0-10 V
Line output	5 V max./50 Ω
Frequency range	20-20,000 Hz (line)
	40-15,000 Hz (mic)
Power supply	DC 22-26 V/0.025 A
Admiss. ambient temp.	0-40 °C
Weight	139 g
Connections	7-pole terminal strip, removable
	1 x RCA L/R (line)
	1 x 6.3 mm jack (mic)