[Ausschreibung]

ATS-162T

16-channel PLL transmitter,

for microphone operation and line audio signals.

• Matching the receivers ATS-162R, TXA-800R and portable amplifiers of the TXA-1000 and TXA-800 series
• Integrated microphone
• Microphone input via 3.5 mm mono jack
• Audio line input via 3.5 mm stereo jack
• Backlit LCD for indicating channel/frequency and battery status
• Belt clip, lanyard
• Power supply via integrated rechargeable lithium battery (1,200 mAh) or low-voltage jack (5 V)
• Transmitting power: ≤ 5 mW (EIRP), operating range: approx. 50 m
• Dimensions: 52 x 88 x 35 mm
• Weight: 88 g

Licence-free in the EU.

[Technische Daten]:

General information	
Type	16-channel mono PLL audio transmitter
Carrier frequency range	863-865 MHz
Admiss. ambient temp.	0-40 °C
Specifications transmitter	
Transmitting power	≤ 5 mW
Operating range	50 m
Power supply transmitter	integrated rech. lithium battery (1,200 mAh), low-voltage jack (5 V)
Width transmitter	52 mm
Height transmitter	88 mm
Depth transmitter	35 mm
Weight transmitter	88 g
Connections transmitter	3.5 mm mono jack (microphone), 3.5 mm mono jack (line in)
Specifications receiver	

Brand: MONACOR

Type: ATS-162T

Quantity: 1

Packing dimensions: