

## Tender text

### ATS-16T

#### 16-channel PLL transmitter,

for microphone operation and line audio signals.

- Integrated microphone
- Supplied with additional electret tie clip microphone
- Audio line input via 3.5 mm mono jack
- Status indication of rech. battery, indication of carrier signal
- Volume level control, belt clip
- Transmitting power:  $\leq 10$  mW (EIRP), operating range: approx. 110 m
- Power supply via 2 x 1.2 V NiMH rech. battery AA size (not supplied) or low-voltage jack (5 V)
- Connection cable 801TG with 3.5 mm plug is available at option for certain JTS headband microphones
- Dimensions: 66 x 111 x 35 mm
- Weight: 81 g

#### Licence-free in the EU.

Specifications:

##### General information

Description	16-channel mono PLL audio transmitter
Carrier frequency range	863-865 MHz
Admiss. ambient temp.	0-40 °C
Specifications transmitter	
Transmitting power	$\leq 10$ mW
Operating range	110 m
Power supply transmitter	2 x 1.2 V NiMH rech. battery AA size, low-voltage jack (5 V)
Width transmitter	66 mm
Height transmitter	111 mm
Depth transmitter	35 mm
Weight transmitter	81 g
Connections transmitter	3.5 mm mono jack (microphone), 3.5 mm mono jack (line in)

Brand: MONACOR

Type: ATS-16T

Quantity: 1

Packing dimensions (W x H x L): 0.15 x 0.04 x 0.16 m

Gross weight: 0.265 kg

Net weight: 0.14 kg

Item weight (w/o accessories): 0.085 kg