

Tender text

ATS-80R

42-channel PLL receiver

- Supplied with matching earphone
- Adjustable headphone output
- Automatic switch-off (power-saving function)
- High-contrast OLED display
- Battery status indication
- Push-to-talk button with 3 operating modes (PTT, PTB, PTM)
- Alarm-off button
- Operating range alert
- Call alert
- Mute function
- Automatic channel lock
- Built-in microphone
- Full duplex communication (release by transmitter)
- Hearing Aid Compatible (HAC)
- Belt clip
- Lanyard
- Power supply via 2 x 1.2 V NiMH rech. battery AA size (not supplied)
- Dimensions: 47 x 109 x 35 mm
- Weight: 53 g

Please consider the regulations and requirements in the country of application.

Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!

Specifications:

General information

Description	42-channel digital PLL receiver
Carrier frequency range	823-832 MHz, 863-865 MHz
Audio frequency range	300-4,500 Hz
Admiss. ambient temp.	0-40 °C
Specifications receiver	
Power supply receiver	2 x 1.2 V NiMH rech. batt. AA size
Width receiver	47 mm
Height receiver	109 mm
Depth receiver	35 mm
Weight receiver	53 g
Connections receiver	3.5 mm jack (earphones)

Brand: MONACOR

Type: ATS-80R

Quantity: 1

Packing dimensions (W x H x L): 0.085 x 0.045 x 0.175 m

Gross weight: 0.142 kg

Net weight: 0.079 kg

Item weight (w/o accessories): 0.053 kg