

# Speakers

## Speaker Systems

### WALL-06T/SW

Order No. 16.3600



### WALL-06T/WS

Order No. 16.3610



#### Pairs of 2-way PA speaker systems

- 100 V wall speaker with plastic cabinet in white (WS) or black (SW)
- 4 power taps as well as switchable to 8 Ω operation
- 16 cm (6") bass-midrange speaker and 25 mm (1") dome tweeter
- Suitable for outdoor applications (IP65)
- Weatherproof
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover



Model	WALL-06T/SW	WALL-06T/WS
Frequency range	70-20,000 Hz	70-20,000 Hz
Power rating (RMS)	32/16/8/4 W (100 V) 50 W (8 Ω)	32/16/8/4 W (100 V) 50 W (8 Ω)
Peak music power output (MAX)	100 W	100 W
Sensitivity	90 dB/W/m	90 dB/W/m
Dimensions	196 x 303 x 250 mm (with bracket)	196 x 303 x 250 mm (with bracket)
Weight	3.5 kg	3.5 kg
Inputs	spring-load. speaker term.	spring-load. speaker term.

### WALL-05T/SW

Order No. 16.3580



### WALL-05T/WS

Order No. 16.3590



#### Pairs of 2-way PA speaker systems

- Wall speaker with plastic cabinet in white (WS) or black (SW)
- 4 power taps as well as switchable to 8 Ω operation
- 13 cm (5") bass-midrange speaker and 12 mm (½") dome tweeter
- Suitable for outdoor applications (IP65)
- Weatherproof
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover



Model	WALL-05T/SW	WALL-05T/WS
Frequency range	80-20,000 Hz	80-20,000 Hz
Power rating (RMS)	16/8/4/2 W (100 V) 40 W (8 Ω)	16/8/4/2 W (100 V) 40 W (8 Ω)
Peak music power output (MAX)	80 W	80 W
Sensitivity	89 dB/W/m	89 dB/W/m
Dimensions	163 x 252 x 203 mm (with bracket)	163 x 252 x 203 mm (with bracket)
Weight	2.6 kg	2.6 kg
Inputs	spring-load. speaker term.	spring-load. speaker term.

### WALL-04T/SW

Order No. 16.3560



### WALL-04T/WS

Order No. 16.3570



#### Pairs of 2-way PA speaker systems

- 100 V wall speaker with plastic cabinet in white (WS) or black (SW)
- 4 power taps as well as switchable to 8 Ω operation
- 10 cm (4") bass-midrange speaker and 12 mm (½") dome tweeter
- Suitable for outdoor applications (IP65)
- Weatherproof
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover



Model	WALL-04T/SW	WALL-04T/WS
Transmission method	100 V	100 V
Frequency range	90-20,000 Hz	90-20,000 Hz
Power rating (RMS)	16/8/4/2 W (100 V) 30 W (8 Ω)	16/8/4/2 W (100 V) 30 W (8 Ω)
Peak music power output (MAX)	60 W	60 W
Sensitivity	87 dB/W/m	87 dB/W/m
Dimensions	130 x 197 x 164 mm (with bracket)	130 x 197 x 164 mm (with bracket)
Weight	1.8 kg	1.8 kg
Inputs	spring-load. speaker term.	spring-load. speaker term.