

Speakers

Speaker Systems

EUL-80/SW

Order No. 16.1190



EUL-80/WS

Order No. 16.1230



EUL-60/SW

Order No. 16.1170



EUL-60/WS

Order No. 16.1180



EUL-30/SW

Order No. 16.1150



EUL-30/WS

Order No. 16.1160



Pair of universal PA speaker systems

- 100 V line technique, 2-way version
- EUL-80... with a 25 mm dome tweeter, EUL-60... and EUL-30... with an 11 mm dome tweeter
- Excellent sound quality
- 6-step power selector switch
- Black (SW) or white (WS) plastic cabinet
- Pivoting mounting bracket
- Bevelled shape of cabinets also allows mounting in corners

Model	EUL-80/SW, EUL-80/WS	EUL-60/SW, EUL-60/WS	EUL-30/SW, EUL-30/WS
Frequency range	40-20,000 Hz	60-20,000 Hz	80-20,000 Hz
Power rating (RMS)	30/15/7.5/4/2 W	15/7.5/4/2/1 W	15/7.5/4/2/1 W
Sensitivity	89 dB/W/m	89 dB/W/m	87 dB/W/m
Dimensions	270 x 370 x 220 mm	215 x 290 x 172 mm	130 x 192 x 115 mm
Weight	5,4 kg	3,4 kg	3,3 kg (pair)
Inputs	spring-load. speaker term.	spring-load. speaker term.	spring-load. speaker term.

ESP-305/SW

Order No. 16.3240



ESP-305/WS

Order No. 16.3250



Miniature PA speaker systems

- 100 V PA speaker system
- 13 cm (5") full range speaker
- Power taps: 20/10/5 W
- Multi-purpose installation options
- 4 x M8 threaded inserts
- 2 x M6 threaded inserts, suitable e.g. for support LST-40
- Use of subwoofer systems is recommended
- Supplied with mounting bracket

Model	ESP-305/SW, ESP-305/WS
Frequency range	140-18,000 Hz
Power rating (RMS)	20/10/5 W
Sensitivity	93 dB/W/m
Dimensions	147 x 146 x 152 mm
Weight	2,1 kg
Inputs	spring-load. speaker term.



ESP-303/SW

Order No. 16.3220



ESP-303/WS

Order No. 16.3230



Miniature PA speaker systems

- 100 V PA speaker system
- 8 cm (3") full range speaker with phase plug
- Power taps: 10/5/2.5 W
- Multi-purpose installation options
- 4 x M8 threaded inserts
- 2 x M6 threaded inserts, suitable e.g. for support LST-40
- Use of subwoofer systems is recommended
- Supplied with mounting bracket

Model	ESP-303/SW, ESP-303/WS
Frequency range	180-20,000 Hz
Power rating (RMS)	10/5/2.5 W
Sensitivity	88 dB/W/m
Dimensions	120 x 120 x 105 mm
Weight	1 kg
Inputs	spring-load. speaker term.

