

SOUND-4BT/WS

Order No. 25.7060



Active 2-way stereo speaker system, with

Bluetooth receiver, 2 x 30 W.

- Set consists of one active and one passive bass-reflex speaker system. Connection of the passive system to the active system via spring-loaded speaker terminals
- Bluetooth receiver V4.0 with APTX
- Active speaker system with integrated 2-channel class D amplifier
- Stereo RCA and 3.5 mm jack input, optical digital input (Toslink), mono sub out via RCA jack
- Supplied with remote control
- 10 cm (4") bass speaker and 25 mm (1") dome tweeter
- Excellent sound characteristics with linear adjustment
- High-gloss lacquered MDF wooden cabinet of high quality



Model	SOUND-4BT/WS
Frequency range	45-20,000 Hz
Rated power (RMS)	2 x 30 W
Input signal	Bluetooth 500 mV/10 kΩ
Sensitivity	85 dB/W/m (each speaker system)
Features	-
Power supply	~ 230 V/50 Hz/170 VA
Dimensions	140 x 215 x 170 mm
Weight	5.2 kg (pair)
Inputs	1 x RCA L/R 1 x 3.5 mm stereo jack 1 x Toslink, optical digital input spring-load, speaker term. for passive sp. system

SOUND-65/SW

Order No. 25.0680



Pair of high-quality active speakers, 2 x 50 W

- 2-way active switching for each speaker system with separate power amplifiers for bass speaker and tweeter (bi-amping)
- Amplifier output power: bass speaker: 30 W, tweeter: 20 W
- High-quality bass-reflex MDF cabinet with black lacquered surface
- 16 cm bass-midrange speaker with glass fibre cone and 25 mm soft dome tweeter
- Tweeter power amplifier with switchable adjustment allows fine adjustment of tweeter level without any losses in the level (-2/-1/0/+1 dB)
- Each speaker system is equipped with an unbalanced RCA input, a balanced XLR input and a jack input (6.3 mm), each to be adjusted via gain control
- Including speaker grille, magnetically attached



Model	SOUND-65/SW
Frequency range	42-20,000 Hz
Rated power (RMS)	50 W
Input signal	720 mV/10 kΩ (bal.) 720 mV/7.7 kΩ (unbal.)
Sensitivity	86 dB/W/m
Power supply	~ 230 V/50 Hz/120 VA
Dimensions	228 x 324 x 295 mm
Weight	7.8 kg
Inputs	1 x RCA, unbal., IN (each speaker system) 1 x XLR, bal., IN (each speaker system) 1 x 6.3 mm jack, bal., IN (each speaker system)