

IT-100TW

Order No. 16.2570



Weatherproof horn speaker (music horn), 2-way technology

- 100 V line technique
- Weatherproof and IP66 certified
- Wideband sound with a distinct bass volume
- 13 cm bass-midrange speaker and 25 mm (1") horn
- Suitable for indoor and outdoor applications
- Robust plastic housing of very low resonance
- Supplied with stainless steel mounting bracket
- 4 power taps, connection via screw terminals

Model	IT-100TW
Frequency range	100-20,000 Hz
Power rating (RMS)	30/15/7.5/3.75 W
Sensitivity	99 dB/W/m
Beam angle	H: 110°/V: 60°
Admiss. ambient temp.	-20 to +50 °C
Dimensions	310 x 215 x 330 mm
Weight	4.42 kg



IT-100RTW

Order No. 16.3340



Weatherproof horn speaker (music horn), 2-way technology

- 100 V line technique with very high tapping power
- Weatherproof and IP66 certified
- Very wideband sound with a distinct bass volume, even at very high volume levels
- 13 cm bass-midrange speaker and 25 mm (1") horn
- Due to round design, consistent radiation pattern in the required area, e.g. ceiling suspension in halls
- Robust plastic housing
- Supplied with mounting bracket and stainless steel screws

Model	IT-100RTW
Frequency range	150-20,000 Hz
Power rating (RMS)	30/15/7.5/3.75 W
Sensitivity	101 dB/W/m
Beam angle	H: 90°/V: 90°
Admiss. ambient temp.	-20 to +50 °C
Dimensions	Ø 300 mm x 360 mm
Weight	4.4 kg



IT-60

Order No. 16.2990



Weatherproof horn speaker, with high power capability.

- 100 V line technique
- Weatherproof and IP66 tested
- Protected against powerful water jets
- Suitable for general indoor and outdoor applications
- Light grey ABS housing (self-extinguishing, complies with standard UL 94V-0)
- Supplied with stainless steel mounting bracket
- Integrated ceramic connection terminal with thermal fuse
- 4 power taps

Model	IT-60
Frequency range	230-9,000 Hz
Power rating (RMS)	60/30/15/7.5 W
Sensitivity	110 dB/W/m
Beam angle	H: 80°/V: 30°
Admiss. ambient temp.	-20 to +50 °C
Dimensions	Ø 305 mm x 385 mm
Weight	4 kg



IT-40

Order No. 16.1360



Weatherproof horn speaker

- 100 V line technique
- Weatherproof and IP66 tested
- Protected against powerful water jets
- Suitable for general indoor and outdoor applications
- Robust plastic housing
- Mounting bracket and screws made of stainless steel
- 5-step power selector switch

Model	IT-40
Frequency range	180-7,000 Hz
Power rating (RMS)	40/30/20/10/5 W
Sensitivity	113 dB/W/m
Beam angle	H: 100°/V: 45°
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	400 x 200 x 420 mm
Weight	3.66 kg

