

IT-130

Order No. 16.1710



Weatherproof horn speaker

- 100 V line technique
- Weatherproof and IP66 tested
- Protected against powerful water jets
- Power selector switch
- For open-air events, industrial use, in workshops

Model	IT-130
Frequency range	250-16,000 Hz
Power rating (RMS)	30/15/10/5/3/1 W
Sensitivity	109 dB/W/m
Admiss. ambient temp.	-20 to +50 °C
Dimensions	290 x 215 x 260 mm
Weight	1.6 kg



IT-115

Order No. 16.1700



Weatherproof horn speaker

- 100 V line technique
- Weatherproof and IP66 tested
- Protected against powerful water jets
- Power selector switch
- For open-air events, industrial use, in workshops

Model	IT-115
Frequency range	280-12,500 Hz
Power rating (RMS)	15/10/5/3/1 W
Sensitivity	108 dB/W/m
Admiss. ambient temp.	-20 to +50 °C
Dimensions	225 x 160 x 235 mm
Weight	1.3 kg



IT-110

Order No. 16.1690



Horn speaker

- 100 V line technique
- Weatherproof and IP66 tested
- Protected against powerful water jets
- Power selector switch
- For open-air events, industrial use, in workshops

Model	IT-110
Frequency range	315-12,500 Hz
Power rating (RMS)	10/5/3/1 W
Sensitivity	105 dB/W/m
Admiss. ambient temp.	-20 to +50 °C
Dimensions	175 x 130 x 185 mm
Weight	1.1 kg



NR-254KS

Order No. 16.2480



Weatherproof horn speaker

- 4 Ω speaker system
- IP66 tested, protected against powerful water jets
- Especially suitable for voice transmissions
- Robust plastic housing of compact size
- Supplied with mounting bracket and mounting screws

Model	NR-254KS
Frequency range	600-14,000 Hz
Power rating (RMS)	12 W
Peak music power output (MAX)	25 W
Sensitivity	107 dB/W/m
Beam angle	H: 90°/V: 90°
Admiss. ambient temp.	-20 to +50 °C
Dimensions	106 x 106 x 88 mm
Weight	1.08 kg

