

Speakers

Weatherproof Speakers

PAB-120WP/SW

Order No. 25.3750



Weatherproof high-performance PA speaker system, 120 W

- 2-way bass-reflex system in an ABS cabinet
- 100 V line technique
- 30 cm (12") PA bass speaker with impregnated paper cone
- 25 mm (1") horn tweeter system
- Front grille with water-repellent gauze
- Metal parts made of stainless steel
- 4 x M10 threaded insert each at the top and bottom for suspended installation
- Stand sleeve
- Ball-proof according to DIN 18032, Part 3

Model	PAB-120WP/SW
Frequency range	42-20,000 Hz
Power rating (RMS)	120/60/30 W
Sensitivity	98 dB/W/m
Admiss. ambient temp.	-10 to +40 °C
Dimensions	370 x 655 x 410 mm
Weight	22.14 kg
Inputs	1 x SPEAKER
Outputs	1 x SPEAKER, par. out



GLS-351/GR


Order No. 16.3080



Weatherproof PA garden speaker „Rock“, stone look, for general PA applications, e.g. in gardens, hotels, restaurants and pubs.

- 100 V line technique or 8 Ω operation
- Robust, glass fibre reinforced plastic cabinet
- 2-way speaker system (200 mm bass speaker and 13 mm tweeter)
- Integrated audio transformer with 4 power taps (30/20/10/5 W)
- Connection cable with luster terminals

Model	GLS-351/GR
Frequency range	60-20,000 Hz
Power rating (RMS)	30/20/10/5 W (100 V) 45 W (8 Ω)
Peak music power output (MAX)	90 W
Sensitivity	88 dB/W/m
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	370 x 300 x 300 mm
Weight	5.8 kg



GLS-301/GR

Order No. 16.3070



Weatherproof PA garden speaker „Rock“, stone look, for general PA applications, e.g. in gardens, hotels, restaurants and pubs.

- Omnidirectional radiation
- 100 V line technique or 8 Ω operation
- Robust, glass fibre reinforced plastic cabinet
- 2-way coaxial speaker system (200 mm bass speaker and 13 mm tweeter)
- Integrated audio transformer with 4 power taps (30/20/10/5 W)
- Connection cable with luster terminals

Model	GLS-301/GR
Frequency range	60-20,000 Hz
Power rating (RMS)	30/20/10/5 W (100 V) 45 W (8 Ω)
Peak music power output (MAX)	90 W
Sensitivity	85 dB/W/m
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	320 x 500 x 310 mm
Weight	9.5 kg

