

40-channel Mono PLL Voice Transmission System, 863-865 MHz

- Economy tour guide system
- Due to the narrow-band frequency range which has been perfectly adapted to voice transmissions, a parallel operation of up to 12 different channels is possible without any interference
- Licence-free in the EU

ATS-50R

Order No. 25.5160

40-channel PLL receiver

- Supplied with matching earpiece
- Adjustable headphone output
- Switches off automatically after not receiving an input signal for 20 minutes (power-saving function)
- LCD for indicating channel, carrier signal and battery status
- Autolock function
- Belt clip

- Power supply via 1 x 1.2 V NiMH rech. battery AA size (not supplied)
- Dimensions: 42 x 98 x 24 mm
- Weight: 45 g

Licence-free in the EU.



ATS-50T

Order No. 25.5170

40-channel PLL transmitter, for microphone operation and audio line signals.

- Integrated microphone
- Supplied with additional electret tie clip microphone
- Audio line input via 3.5 mm stereo jack
- LCD for indicating channel and battery status
- Mute button
- Belt clip
- Transmitting power: ≤ 10 mW (EIRP), operating range: approx. 100 m

- Power supply via 1 x 1.2 V NiMH rech. battery AA size (not supplied)
- Dimensions: 42 x 98 x 24 mm
- Weight: 45 g

Licence-free in the EU.



ATS-50PS

Order No. 25.0080

Intelligent PWM quick-charge station, for simultaneously charging rech. batteries (NC, NiMH) of two devices from the ATS-50 series.

- Average charging time, depending on capacity and condition of the rechargeable batteries used: approx. 3-4 hours, e.g. for 1,300 mAh rech. batteries

- Each slot with LED for indicating a fault and battery charging status
- Mechanical reverse polarity protection
- Including plug-in power supply



ATS-25C

Order No. 25.5180

Transport case with integrated charging function, for transmitters and receivers of the ATS-50 series.

- For simultaneously charging rech. batteries of up to 25 devices

- Each slot with LED for indicating battery charging status
- Transport case with black imitation leather cover
- Supplied with matching power supply
- Dimensions: 442 x 160 x 290 mm
- Weight: 5.2 kg

