

ECM-306B/SW

Order No. 23.5790

ECM-306B/WS

Order No. 23.5800

Boundary microphones

- On/off switch with power LED
- Low cut and 10 dB attenuation, switchable
- Integrated electronics for direct connection to a phantom power supply = 17-48 V
- Electronically balanced AF output
- With 6 m connection cable, 3-pole mini XLR/XLR
- Supplied in a foam-padded plastic case

Model	ECM-306B/SW, ECM-306B/WS
Polar pattern	semi-supercardioid
System	electret
Audio frequency range	30-20,000 Hz
Nominal impedance	250 Ω
Sensitivity	22 mV/Pa
Max. sound pressure	130 dB
Power supply	= 17-48 V, phantom power
Dimensions	90 x 16 x 90 mm
Weight	200 g
Cable	6 m
Connection	3-pole mini XLR/XLR



ECM-306B/SW = black version

ECM-306B/WS = white version

ECM-302B

Order No. 23.2370

ECM-302B/WS

Order No. 23.3630

Boundary microphones

- Integrated electronics for direct connection to a phantom power supply = 17-48 V
- Transformer-balanced AF output
- With 6 m connection cable, 3-pole mini XLR/XLR

Model	ECM-302B	ECM-302B/WS
Polar pattern	semi-cardioid	semi-cardioid
System	electret	electret
Audio frequency range	30-20,000 Hz	30-20,000 Hz
Nominal impedance	250 Ω	250 Ω
Sensitivity	22 mV/Pa	22 mV/Pa
Max. sound pressure	140 dB	140 dB
Power supply	= 17-48 V, phantom power	= 17-48 V, phantom power
Dimensions	Ø 120 mm x 22 mm	Ø 120 mm x 22 mm
Weight	350 g	350 g
Cable	6 m	6 m
Connection	3-pole mini XLR/XLR	3-pole mini XLR/XLR



ECM-302B = black version

ECM-302B/WS = white version

ECM-304BD

Order No. 23.2510

ECM-304BD/WS

Order No. 23.3270

Boundary microphones

- Switchable polar pattern: cardioid/omnidirectional
- Voltage supply via 1.5 V button cell (not supplied). Phantom power via mixer not required
- With 4 m connection cable, 3.5/6.3 mm plug

Model	ECM-304BD	ECM-304BD/WS
Polar pattern	cardioid/omnidir.	cardioid/omnidir.
System	electret	electret
Audio frequency range	30-20,000 Hz	30-20,000 Hz
Nominal impedance	600 Ω/1,000 Ω	600 Ω/1,000 Ω
Sensitivity	7 mV/Pa	7 mV/Pa
Power supply	1.5 V button cell (LR44)	1.5 V button cell (LR44)
Admiss. ambient temp.	0-40 °C	0-40 °C
Dimensions	70 x 96 x 20 mm	70 x 96 x 20 mm
Weight	290 g	285 g
Cable	4 m	4 m
Connection	3.5/6.3 mm plug	3.5/6.3 mm plug



ECM-304BD = black version

ECM-304BD/WS = white version

ECM-10/SW

Order No. 23.2720

ECM-10/WS

Order No. 23.2730

Built-in electret microphones

- Particularly suitable for PA applications
- Metal housing
- Black (SW) or white (WS) cartridge cover

Model	ECM-10/SW, ECM-10/WS
Polar pattern	omnidir.
System	electret
Audio frequency range	30-17,000 Hz
Nominal impedance	300 Ω
Sensitivity	2.3 mV/Pa
Max. sound pressure	110 dB
Power supply	= 9-48 V, phantom power
Housing material	metal
Dimensions	Ø 30 mm x 71 mm
Weight	92 g
Connection	XRL, bal.

