

FGA-30

Order No. 21.2430

Ground isolator

- Prevents hum loops
- Galvanically isolated inputs and outputs
- 2 RCA jacks
- 3.5 mm stereo plug
- Input/output impedance: 20 k Ω
- Frequency range: 20-30,000 Hz

- THD: < 0.01%
- Transmission ratio: 1:1
- \varnothing 24 mm x 38 mm, 32 g
- Length including connection cable: approx. 40 cm



FGA-30M

Order No. 21.3010

Ground isolator

- Prevents hum loops
- Galvanically isolated inputs and outputs
- 2 RCA plugs
- 3.5 mm stereo plug
- Input/output impedance: 20 k Ω
- Frequency range: 20-30,000 Hz

- THD: < 0.01%
- Transmission ratio: 1:1
- \varnothing 24 mm x 38 mm, 32 g
- Length including connection cable: approx. 115 cm



FGA-35

Order No. 21.2420

Ground isolator

- Prevents hum loops
- Galvanically isolated inputs and outputs
- 2 x 3.5 mm stereo plug
- Input/output impedance: 20 k Ω
- Frequency range: 20-30,000 Hz
- THD: < 0.01%

- Transmission ratio: 1:1
- \varnothing 24 mm x 38 mm, 32 g
- Length including connection cable: approx. 80 cm



FGA-40MF

Order No. 21.3050

Ground isolator

- Prevents hum loops
- Galvanically isolated inputs and outputs
- 2 RCA jacks
- 2 RCA plugs
- Input/output impedance: 20 k Ω
- Frequency range: 20-30,000 Hz

- THD: < 0.01%
- Transmission ratio: 1:1
- \varnothing 24 mm x 38 mm, 32 g
- Length including connection cable: approx. 40 cm



FGA-40HQ

Order No. 06.6380

High-end ground isolator, for preventing signal interference and hum loops which may occur, e.g. when connecting the car radio to an amplifier.

- Gold-plated RCA jacks
- Input/output impedance: 12 k Ω
- Frequency range: 20-30,000 Hz
- THD: < 0.001%

- Transmission ratio: 1:1
- 42 x 29 x 96 mm, 110 g



FGA-40

Order No. 06.4370

Ground isolator, for preventing signal interference and hum loops which may occur, e.g. when connecting the car radio to an amplifier.

- Galvanically isolated inputs and outputs
- RCA plugs and RCA jacks
- Input/output impedance: 15 k Ω
- Frequency range: 20-30,000 Hz

- THD: < 0.001%
- Transmission ratio 1:1
- \varnothing 35 mm x 65 mm, 65 g

