RL-1ENABDS

Order No. 16.3690

100V EN 54 NEW

PA A/B sound projector for wall mounting, with EN 54-24 certification for evacuation systems with A/B speaker distribution according to EN 60849.

- 100 V line technique
- 13 cm full range speaker with dual voice coil
- 2 x 100 V transformator with power taps on the cable 6/3/1.5 W
- Connection via 2 x 4-core cable (length: 1.5 m)
- Metal housing with front protective grille
- Supplied with pan/tilt bracket and mounting accessories

Model	RL-1ENABDS
Frequency range	80-20,000 Hz
Power rating (RMS)	2 x 6/3/1.5 W
Sensitivity	93 dB/W/m
Beam angle	130°
Housing material	aluminium
Colour	white
Mounting device	bracket
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 144 mm x 210 mm
Weight	2.3 kg

RL-1EN

Order No. 16.3680

100V EN 54 NEW

PA sound projector for wall mounting, with EN 54-24 certification.

- 100 V line technique
- 13 cm full range speaker
- 100 V transformer with power taps on the cable 6/3/1.5 W
- Connection via 4-core cable (length: 1.5 m)
- Metal housing with front protective grille
- Supplied with pan/tilt bracket and mounting accessories

Model	RL-1EN
Frequency range	80-20,000 Hz
Power rating (RMS)	6/3/1.5 W
Sensitivity	93 dB/W/m
Beam angle	130°
Housing material	aluminium
Colour	white
Mounting device	bracket
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 144 mm x 210 mm
Weight	1.9 kg

DAP-20-130/T

Order No. 16.3700

100V EN 54 IP66 NEW

Weatherproof PA sound projector, for wall mounting and with EN 54-24 certification.

- 100 V line technique
- 13 cm waterproof full range speaker
- 100 V transformer with power taps 20/10/5/2.5 W
- Connection via ceramic terminal and thermal fuse in the junction box (cable length: 1 m)
- ABS plastic housing with front protective grille
- Robust aluminium mounting bracket

Model	DAP-20-130/T
Frequency range	150-20,000 Hz
Number of speakers	2
Power rating (RMS)	20/10/5/2.5 W
Sensitivity	90 dB/W/m
Beam angle	110°
Housing material	ABS plastic
Colour	white
Mounting device	bracket
Admiss. ambient temp.	-20 to +90 °C
Dimensions	Ø 145 mm x 222 mm
Weight	1.367 kg

DA-10-260/T

Order No. 16.3710

100V EN 54 2 DIR IP65 NEW

Weatherproof PA sound projector, for wall mounting and with EN 54-24 certification.

- 100 V line technique
- 2 x 13 cm full range speaker for bi-directional radiation
- 100 V transformer with power taps 10/6/3/1.5 W
- Connection via ceramic terminals with thermal fuse in the mounting base
- Robust plastic-coated aluminium housing with front protective grille
- Robust vandal-resistant aluminium mounting base

Model	DA-10-260/T
Frequency range	120-17,000 Hz
Number of speakers	2
Power rating (RMS)	12/6/3/1.5 W
Sensitivity	93 dB/W/m
Beam angle	150°
Housing material	aluminium
Colour	white, RAL 9010
Mounting device	mounting base
Admiss. ambient temp.	-20 to +90 °C
Dimensions	166 x 197 x 161 mm
Weight	2.31 kg