

ETS-442TW/WS

Order No. 16.3140



ETS-432TW/WS

Order No. 16.3130



ETS-422TW/WS

Order No. 16.3120



Weatherproof PA column speakers, with a top-quality sound.

- Weatherproof and hose-proof, extruded aluminium cabinet
- 100 V line technique
- 2-way version (with additional integrated tweeter for a clearly improved sound)
- Integrated crossover network
- Aluminium front grille
- Supplied with a robust tiltable and movable aluminium wall bracket
- Connection via cable with 4 power taps



Model	ETS-442TW/WS	ETS-432TW/WS	ETS-422TW/WS
Frequency range	110-20,000 Hz	120-20,000 Hz	130-20,000 Hz
Number of speakers	8+1	6+1	4+1
Power rating (RMS)	40/20/10/5 W	30/15/7.5/3.75 W	20/10/5/2.5 W
Sensitivity	93 dB/W/m	93 dB/W/m	92 dB/W/m
Admiss. ambient temp.	-20 to +50 °C	-20 to +50 °C	-20 to +50 °C
Dimensions	124 x 1,016 x 108 mm	124 x 813 x 108 mm	124 x 610 x 108 mm
Weight	6.9 kg	5.5 kg	4 kg

ETS-240TW/WS

Order No. 16.2960



ETS-220TW/WS

Order No. 16.2950



ETS-210TW/WS

Order No. 16.2940



PA column speakers, in extruded aluminium cabinets.

- Weatherproof and hose-proof
- 100 V line technique
- 2-way version (with additional integrated tweeters for a clearly improved sound)
- Connection cable with 5-step power taps
- 2 x M6 threaded bushing
- Aluminium front grille
- Supplied with mounting brackets



Model	ETS-240TW/WS	ETS-220TW/WS	ETS-210TW/WS
Frequency range	150-20,000 Hz	150-20,000 Hz	170-20,000 Hz
Number of speakers	8+4	4+2	2+1
Power rating (RMS)	40/30/20/10/5 W	20/15/10/5/2.5 W	10/5/2.5/1.25/0.63 W
Sensitivity	90 dB/W/m	89 dB/W/m	86 dB/W/m
Admiss. ambient temp.	-20 °C to +50 °C	-20 °C to +50 °C	-20 °C to +50 °C
Dimensions	80 x 846 x 70 mm	80 x 469 x 70 mm	80 x 280 x 70 mm
Weight	2.7 kg	1.6 kg	1 kg