

NR-60KS

Order No. 0163010



Weatherproof horn speaker, with high power capability.

- 16 Ω speaker system
- IP66 tested, protected against powerful water jets
- Suitable for general indoor and outdoor applications
- Robust light grey plastic housing
- Aluminium mounting bracket

Model	NR-60KS
Total power rating	60 W
Power rating (RMS)	30 W
Frequency range	340-10,000 Hz
Sensitivity	103 dB/W/m
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 146 mm x 160 mm
Weight	2 kg



NR-40KS

Order No. 0161370



Weatherproof horn speaker

- 16 Ω speaker system
- IP66 tested, protected against powerful water jets
- Suitable for general indoor and outdoor applications
- Robust plastic housing
- Mounting bracket and screws made of stainless steel

Model	NR-40KS
Total power rating	60 W
Power rating (RMS)	30 W
Frequency range	180-7,000 Hz
Sensitivity	113 dB/W/m
Beam angle	H: 110°/V: 45°
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	400 x 200 x 385 mm
Weight	3 kg



NR-35KS

Order No. 0160250



Horn speaker

- Moisture-proof
- 8 Ω speaker system

Model	NR-35KS
Total power rating	40 W
Power rating (RMS)	20 W
Frequency range	300-12,000 Hz
Sensitivity	107 dB/W/m
Beam angle	H: 100°/V: 50°
Admiss. ambient temp.	0-40 °C
Dimensions	280 x 170 x 215 mm
Weight	1.4 kg



NR-33KS

Order No. 0160650



Weatherproof horn speaker

- IP66 tested, protected against powerful water jets
- 8 Ω speaker system
- Suitable for general indoor and outdoor applications
- Robust plastic housing
- Mounting bracket and screws made of stainless steel

Model	NR-33KS
Total power rating	25 W
Power rating (RMS)	12 W
Frequency range	275-7,000 Hz
Sensitivity	106 dB/W/m
Beam angle	H: 100°/V: 50°
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	250 x 145 x 272 mm
Weight	1.5 kg

