

RTX-4

Order No. 0259630



Bluetooth audio transceiver

- Switchable between transmitting mode and receiving mode
- Volume control via connected devices (passive operation)
- Supports aptX and AAC audio codecs for optimum sound
- Supports aptX Low Latency for low-latency transmission
- Automatic pairing

Model	RTX-4
Frequency range	20-20,000 Hz
Bluetooth	4.1, Class 2
Operating range	≤ 10 m
Profiles	A2DP
Codecs	SBC, MP3, aptX, aptX Low Latency, AAC
Power supply	via micro USB
Dimensions	104 x 20 x 24 mm
Weight	43 g
Connections	2 x Toslink, optical/digital 2 x 3.5 mm stereo jack, analogue 1 x micro USB



RTX-1

Order No. 0257810



Bluetooth audio transmitter/receiver

- Switchable between transmitting mode and receiving mode:
 - Use as transmitter for music reproduction with Bluetooth-enabled end devices, e.g. headphones or speakers
 - Use as receiver for reception of audio signals via Bluetooth and subsequent transmission via connection jacks, e.g. to a stereo system
- LED status indication

Model	RTX-1
Bluetooth	Bluetooth V2.1, Class 2 (Rx), Class 1 (Tx)
Operating range	10 m (Rx), 30 m (Tx)
Profiles	A2DP, AVRCP
Power supply	via encl. power supply
Dimensions	110 x 25 x 61 mm
Weight	104 g
Connections	1 x 3.5 mm stereo jack (line out), 1 x 3.5 mm stereo jack (line in), 1 x RCA L/R (line out), 1 x RCA L/R (line in), 1 x micro USB (power supply)



WSA-2

Order No. 0255790



Bluetooth audio receiver,

- Multipoint Bluetooth (simultaneous pairing of 2 units)
- Scope of delivery: wireless audio streamer, plug-in PSU, audio cable RCA to 3.5 mm stereo plug

Model	WSA-2
Bluetooth	version 3.0, class 2
Operating range	10 m (typ.) 20 m (clear view)
Profiles	A2DP
Power supply	via encl. power supply
Dimensions	50 x 24 x 56 mm
Weight	33 g
Connections	Outputs: 1 x RCA L/R 1 x 3.5 mm jack, stereo



WSA-10BT

Order No. 0255800



Bluetooth audio receiver, for playing tracks from mobile audio devices directly on your audio system.

- Audio streaming directly from any Bluetooth device
- Supports aptX for an improved audio quality
- Autopairing
- Up to 10 paired devices can be stored
- Optical and coaxial digital output, analogue line level output

Model	WSA-10BT
Frequency range	20-20,000 Hz
THD	0.05%
Channel separation	45 dB
Bluetooth	4.0, class 2
Operating range	10 m (typ.) 20 m (clear view)
Profiles	A2DP
Power supply	via encl. power supply
Dimensions	91 x 25 x 57 mm
Weight	60 g
Connections	Outputs: 1 x Toslink, optical/digital 1 x RCA, digital 1 x 3.5 mm stereo jack, analogue



WSA-20BT

Order No. 0257130



Bluetooth audio receiver, for playing music tracks from mobile audio devices directly on your audio system.

- Audio streaming directly from any Bluetooth device
- Analogue line level output via 6.3 mm jacks L/R
- LED for status indication
- Integrated magnets for attaching it e.g. to a device housing

Model	WSA-20BT
Frequency range	20-20,000 Hz
THD	≤ 0.01%
Channel separation	≥ 75 dB
Bluetooth	Bluetooth V4.0, class 2
Operating range	≤ 10 m
Profiles	HFP, HSP, A2DP, AVRCP, DI
Power supply	via encl. power supply
Dimensions	116 x 35 x 86 mm
Weight	117 g
Connections	Outputs: 1 x 6.3 mm stereo jack L/R, analogue

