

TXA-800HT

Order No. 0172260

Hand-held microphone with integrated multi-frequency transmitter, with UHF PLL technology.

Matching portable amplifier systems of the TXA-1000 and TXA-800 series.

- Dynamic microphone cartridge, cardioid polar pattern
- 16 selectable UHF frequencies (863.1-864.9 MHz)
- Sensitivity to be adjusted in 2 steps
- Mute function
- Backlit LCD for indicating channel/frequency and battery status
- Transmitting power: 10 mW (EIRP)
- Power supply via 2 x 1.5 V battery AA size (not supplied)
- Supplied with 4 coloured caps to be pushed on

Model	TXA-800HT
Polar pattern	cardioid
System	dynamic
Carrier frequency range	863.1-864.9 MHz
Transmitting power	10 mW
Power supply	2 x 1.5 V batt. AA size
Audio frequency range	70-16,000 Hz
Dimensions	Ø 46 mm x 265 mm
Weight	250 g

Licence-free in the EU.



TXA-800HSE

Order No. 0172250

Multifrequency pocket transmitter, with UHF PLL technology. Matching portable amplifier systems of the TXA-1000 series, TXA-800 series and TXA-800R.

- 1 headband microphone (omnidir. char.), 1 tie clip microphone (cardioid char.)
- 16 selectable UHF frequencies (863.1-864.9 MHz)
- Metal housing
- Microphone connection via 3-pole mini XLR jack
- Audio line input via 3.5 mm stereo jack
- Sensitivity to be adjusted in 3 steps
- Mute function
- Backlit LCD for indicating channel/frequency and battery status
- Transmitting power: 10 mW (EIRP)
- Power supply via 2 x 1.5 V battery AA size (not supplied)
- Belt clip

Model	TXA-800HSE
Carrier frequency range	863.1-864.9 MHz
Audio frequency range	70-16,000 Hz
Admiss. ambient temp.	0-40 °C
Transmitting power	10 mW
Operating range	30 m
Power supply transmitter	2 x 1.5 V batt. AA size
Dimensions transmitter	65 x 95 x 30 mm
Weight transmitter	110 g
Connections transmitter	1 x 3-pole mini XLR

Licence-free in the EU.



TXA-820MT

Order No. 0179080

Multifrequency transmitter module, with UHF PLL technology.

For retrofitting amplifier systems of the TXA-820 series or for setting up wireless audio transmission paths.

- 16 selectable UHF frequencies (863-865 MHz)
- Volume control
- LCD for indicating selected channel/frequency
- LEDs for indicating carrier signal and audio signal

Model	TXA-820MT
Description	multifrequency transmitter module
Carrier frequency range	863-865 MHz
Admiss. ambient temp.	0-40 °C
Transmitting power	≤ 10 mW
Operating range	approx. 30 m
Power supply transmitter	≈ 12 V/120 mA
Dimensions transmitter	88 x 37 x 113 mm
Weight transmitter	80 g

Licence-free in the EU.

