

## Professional 16-channel Mono PLL Audio Transmission System, 863-865 MHz

- Compatible with portable amplifier systems of the TXA-820 and TXA-1020 series
- Can be combined with the TXA-820 and TXA-1020 series, but also suitable as a tour guide system and for any other application in which a certain audio source or voice source is to be distributed to one or more receivers
- Licence-free in the EU.

### TXA-802SR

Order No. 0172990

**2-channel multifrequency receiver**, with UHF PLL technology.

- Matching the transmitters TXA-800HT, TXA-800HSE, TXA-800ST and ATS-12HT
- 2 x 16 selectable UHF frequencies (863.1-864.9 MHz) with diversity system
- Scan function for free channel
- Volume control
- LCD for indicating selected channel and carrier signal
- Balanced XLR output and 6.3 mm jack output
- 482 mm (19") rack installation of 2 devices is possible with supplied mounting brackets



- Power is provided via enclosed plug-in power supply
- Dimensions: 215 x 50 x 210 mm
- Weight: 1.2 kg

**Licence-free in the EU.**

### TXA-800R

Order No. 0172590

**16-channel PLL receiver**

- Matching the transmitters TXA-800ST, TXA-800HT, TXA-800HSE, ATS-16T and portable amplifier system TXA-802CD with integrated wireless transmitter
- 16 selectable UHF frequencies (863.1-864.9 MHz)
- Adjustable headphone output
- Line output level adjustable in 3 steps
- Metal housing
- Power supply via 2 x 1.5 V battery AA size or NiMH rech. battery (not supplied)
- Scope of delivery includes earphones with rubber ear hook
- Belt clip



**Licence-free in the EU.**

### TXA-802PS

Order No. 0255860

**PWM quick-charge station**, for simultaneously charging the rechargeable batteries (NC, NiMH) of one multifrequency pocket transmitter TXA-800HSE or the receiver TXA-800R and one hand-held microphone with multifrequency transmitter TXA-800HT.

- Average charging time, depending on capacity and condition of the rechargeable batteries used: approx. 4-5 hours, e.g. for 1,600 mAh



- rech. batteries
- Each slot with LED for indicating battery charging status
- Supplied with plug-in PSU

### TXA-800PS

Order No. 0252140

**Intelligent PWM quick-charge station**, for simultaneously charging rech. batteries (NC, NiMH) of two receivers TXA-800R, also suitable for transmitter TXA-800HSE.

- Average charging time, depending on capacity and condition of the rechargeable batteries used: approx. 3-4 hours, e.g. for 1,300 mAh



- Each slot with LED for indicating a fault and battery charging status
- Mechanical reverse polarity protection
- Including plug-in power supply

### TXA-12C

Order No. 0252150

**Transport case with intelligent PWM quick-charge function**, for receiver TXA-800R and transmitter TXA-800HSE.

- For simultaneously charging rech. batteries (NC, NiMH) of up to 12 units
- Average charging time, depending on capacity and condition of the rechargeable batteries used: approx. 5-6 hours, e.g. for 1,300 mAh rech. batteries
- Each slot with LED for indicating a fault and battery charging status
- Mechanical reverse polarity protection



- Wooden case with black imitation leather cover
- Supplied with matching power supply
- Dimensions: 300 x 170 x 280 mm

**Supplied w/o devices.**

### TXA-36C

Order No. 0252160

**Transport case with intelligent PWM quick-charge function**, for receiver TXA-800R and transmitter TXA-800HSE.

- For simultaneously charging rech. batteries (NC, NiMH) of up to 36 devices
- Average charging time, depending on capacity and condition of the rech. batteries used: approx. 5-6 hours, e.g. for 1,300 mAh rech. batteries
- Each slot with LED for indicating a fault and battery charging status
- Mechanical reverse polarity protection



- Lockable plastic transport case fitted with castors
- Including matching switch-mode power supply
- Dimensions: 860 x 230 x 350 mm

**Supplied w/o devices.**