

ATS-80ST

Order No. 0179440



42-channel stationary PLL transmitter, for microphone operation and audio line signals. In combination with ATS-80R, also suitable for interpretation systems.

- Stereo audio line input via RCA L/R
- Microphone input via comb. jack (XLR/6.3 mm jack)
- Mono audio line output via RCA
- Loop input and loop output via 6.3 mm jack
- Adjustable headphone output for monitoring
- Removable antenna (TNC)
- Supports Bluetooth
- USB audio programming interface
- High-contrast OLED display
- Channel name and ID can be edited
- Adjustable transmitting power (high: ≤ 20 mW/low: ≤ 10 mW)
- Operating range: approx. 100 m

- Power is provided via encl. plug-in power supply
- Dimensions: 215 x 51 x 210 mm
- Weight: 1.25 kg

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!



ATS-80EM

Order No. 0221370



Earphone microphone

- Suitable for 42-channel PLL transmitter ATS-80T
- Electret headband microphone
- Mono earphone with ring holder for a secure fit
- Clip
- 1 m connection cable with 3.5 mm plug



ATS-85PS

Order No. 0179470



Charging station, for simultaneously charging rech. batteries of up to 5 devices from the ATS-80 series.

- Each slot with LED for indicating battery charging status
- Mechanical reverse polarity protection
- Matrix LCD
- Metal housing

- Including plug-in power supply
- Supplied with programming software for ATS-80R and ATS-80T (SYNC function)



ATS-825C

Order No. 0179450



Transport case with integrated charging function and programming function, for transmitters and receivers from the ATS-80 series.

- For simultaneously charging rech. batteries of up to 25 devices
- Each slot with LED for indicating battery charging status

- Mechanical reverse polarity protection
- Matrix LCD
- Transport case with carrying handle, lockable
- Supplied with matching power supply
- Supplied with programming software for ATS-80R and ATS-80T (SYNC function)

Supplied w/o devices.



ATS-850PS

Order No. 0179460



Charging station, for simultaneously charging rech. batteries of up to 50 devices from the ATS-80 series.

- Each slot with LED for indicating battery charging status
- Mechanical reverse polarity protection
- Fan cooling
- Matrix LCD

- Metal housing
- 482 mm (19") rack installation
- Supplied with programming software for ATS-80R and ATS-80T (SYNC function)

