

Speakers

Column Speakers

ETS-120SL/WS

Order No. 0163450



Pair of line array design speakers, 4 Ω, in slimline extruded aluminium cabinets.

- Elegant slimline design
- Cross-sectional area not much bigger than a 1 Euro coin
- New type of speaker systems with magnetostatic drive and flat cone speakers
- Very wide bandwidth reproduction with an excellent sound quality
- High transmission range due to line array system
- Connection via screw terminal
- Fine-meshed front grille with fleece lining
- Supplied with mounting brackets and connection cables

Model	ETS-120SL/WS
Total power rating	80 W
Power rating (RMS)	40 W
Impedance	4 Ω
Frequency range	120-20,000 Hz
Number of speakers	4
Sensitivity	88 dB/W/m
Beam angle	H: 160°/V: 40°
Dimensions	36 x 1,210 x 22 mm
Weight	0.95 kg



ESUB-6W/WS

Order No. 0259930



ESUB-6W/SW

Order No. 0259920



Wall-mount PA subwoofer, 2 x 60 W

- Dual vented band-pass subwoofer for unobtrusive wall mounting
- 16 cm (6") high-performance speaker of long excursion with dual voice coil
- 100 V line technique with 4 power taps: 60/30/15 W
- Impedance switchable to 4 Ω + 4 Ω
- Frequency range: 50-200 Hz (-6 dB), integrated crossover network
- 2 x 4 Ω satellite speaker outputs with high-pass filter
- Connection via Euroblock connectors
- High-quality black or white coating
- Supplied with robust wall bracket



Model	ESUB-6W/WS	ESUB-6W/SW
Total power rating	2 x 125 W	2 x 125 W
Power rating (RMS)	60/30/15 W (100 V) 2 x 60 W (4 Ω)	60/30/15 W (100 V) 2 x 60 W (4 Ω)
Impedance	4 Ω + 4 Ω	4 Ω + 4 Ω
Frequency range	50-200 Hz	50-200 Hz
Number of speakers	1	1
Sensitivity	87 dB/W/m	87 dB/W/m
Dimensions	450 x 350 x 180 mm	450 x 350 x 180 mm
Weight	12.25 kg	12.15 kg