## Tender text

**CDX1-1430**

**PA horn driver, 50 W, 8 Ω**

• 25 mm (1") horn driver
• Standard 2-hole screw mounting
• Neodymium drive system with cooling
• Wide and extra linear frequency response
• Very high sound pressure level with lowest distortions
• From approx. 3,000 Hz already, this driver provides a very high-quality sound in 2-way arrangements, even with 38 cm (15") bass speakers
• Suitable for horns MRH-200 and MRH-180

Specifications:

| | |
|---|---|
| Impedance (Z) | 8 Ω |
| Frequency range | fx-20,000 Hz |
| Resonant frequency (fs) | 2,000 Hz |
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | 2,500 Hz |
| Power rating (RMS) | 50 W |
| Peak music power output (MAX) | 100 W |
| SPL | 108 dB/W/m |
| Voice coil diameter | Ø 35 mm |
| Magnet diameter | Ø 75 mm |
| Mounting cutout | dep. on horn |
| Mounting depth | dep. on horn |
| Mounting hole diameter | Ø 76 mm |
| Dimensions | Ø 75 mm x 75 mm |
| Colour | black |
| Admiss. ambient temp. | 0-40 °C |
| Weight | 0.495 kg |
| Packing unit | 1 |
| Type of speaker | 1" |
| Packing dimensions (W x H x L) | 0.13 x 0.085 x 0.11 m |
| Gross weight | 0.52 kg |
| Net weight | 0.495 kg |

Brand: CELESTION

Type: CDX1-1430

Quantity: 1

Packing dimensions (W x H x L): 0.13 x 0.085 x 0.11 m

Gross weight: 0.52 kg

Net weight: 0.495 kg

Item weight (w/o accessories): 0.495 kg