Tender text

DTTA-2

Dante® I/O box,

for converting analogue audio signals into Dante® streams.

• 2 x microphone/line input (XLR, bal.)
• 1 x aux input (3.5 mm stereo jack)
• 1 x Dante® output (EtherCon/RJ45)
• 1 x monitor output (3.5 mm stereo jack) with 56 dB crosstalk attenuation to the input signal
• Gain adjustable via recessed potentiometer (0-60 dB)
• Individually switchable 12 V phantom power for the inputs
• Encoding/decoding: 16/24/32 bits
• Sampling rates: 44.1/48/88.2/96 kHz
• Frequency range: 20-20,000 Hz
• LED indication for level control, PoE, external power supply and link
• Metal housing
• Power is provided via PoE or optional power supply
• Dimensions: 81 x 45 x 153 mm
• Weight: 400 g

System requirements Dante®: Windows* 7/8.1/10 or MacOS 10.9.5/10.10.5/10.11

The brand Dante® as well as the Dante® software which may have been integrated into these products are licenced by Audinate Pty Ltd.

Specifications:

Description	Dante® I/O box
Colour	black
Material	metal
Power supply	PoE or DC 12 V/500 mA
Admiss. ambient temp.	0-40 °C
Dimensions	81 x 45 x 153 mm
Weight	351 g
Connections	2 x XLR, bal. (in 1, in 2), 1 x 3.5 mm stereo jack (aux input), 1 x EtherCon/RJ45 (Dante® output), 1 x 3.5 mm stereo jack (monitor output)
Other features	12 V phantom power, input sensitivity: 5 mV-4 V/18 kΩ
Packing unit	1

Brand: MONACOR

Type: DTTA-2

Quantity: 1

Packing dimensions (W x H x L): 0.19 x 0.07 x 0.13 m

Gross weight: 0.464 kg

Net weight: 0.351 kg

Item weight (w/o accessories): 0.351 kg