

Tender text

ECM-250

Electret microphone set,

consisting of two overhead electret microphones.

- Optimised for sound pickup of drum combinations and percussion instruments
- Short-bodied microphones
- Low cut switch, selectable 10 dB attenuation
- 48 V phantom power
- Including microphone holder with 16 mm ($\frac{5}{8}$ ") tripod socket and 9 mm ($\frac{3}{8}$ ") adapter screw
- Supplied in a practical plastic case

Specifications:

Description	overhead microphone
Transmission method	cable
Polar pattern	cardioid
System	electret
Audio frequency range	50-16,000 Hz
Nominal impedance	200 Ω
Sensitivity	18/5.6 mV/Pa
S/N ratio	66 dB
Max. sound pressure	130 dB
Power supply	DC 48 V, phantom power
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 19 mm x 80 mm
Weight	25 g
Connection	XLR, quasi-balanced
Packing dimensions (W x H x L)	0.16 x 0.085 x 0.275 m
Gross weight	0.515 kg
Net weight	0.145 kg

Brand: IMG STAGELINE

Type: ECM-250

Quantity: 1

Packing dimensions (W x H x L): 0.16 x 0.085 x 0.275 m

Gross weight: 0.515 kg

Net weight: 0.145 kg

Item weight (w/o accessories): 0.025 kg