

## Tender text

### EDL-80DT

#### Active 2-way flush-mount ceiling speaker,

with integrated Dante<sup>®</sup> module.

- 30 W amplifier
- 20 cm (8") bass speaker with glass fibre cone, 2.5 cm (1") dome tweeter
- Decoding: 16/24/32 bits
- Sampling rates: 44.1/48/88.2/96 kHz
- Power supply via PoE (Power over Ethernet)
- For a ceiling thickness up to 4 cm
- Mounting cutout: Ø 240 mm
- Mounting depth: 225 mm incl. space requirement for network connection

System requirements Dante<sup>®</sup>: Windows\* 7/8.1/10 or MacOS 10.9.5/10.10.5/10.11

The brand Dante<sup>®</sup> as well as the Dante<sup>®</sup> software which may have been integrated into these products are licenced by Audinate Pty Ltd.

#### Specifications:

Active/passive	active
Transmission method	Dante <sup>®</sup>
Power rating (RMS)	30 W
Frequency range	100-20,000 Hz
Input signal	DANTE <sup>®</sup>
System	2-way
Bass speaker	1 x 20 cm
Tweeter	1 x 2.5 cm
Number of speakers	2
Speaker size	20 cm (8")
Sensitivity	93 dB/W/m
Max. rated SPL	105 dB
Radiation angle, horizontal	100°
Radiation angle, vertical	100°
Housing material	metal, plastic
Colour	white
Mounting device	ceiling suspension
Admiss. ambient temp.	0-40 °C
Power supply	PoE via RJ45
Dimensions	Ø 272 mm x 187 mm
Width	Ø 272 mm
Depth	187 mm
Weight	2.7 kg
Inputs	RJ45

Packing dimensions (W x H x L)	0.31 x 0.23 x 0.32 m
Gross weight	3.64 kg
Net weight	2.73 kg

Brand: MONACOR

Type: EDL-80DT

Quantity: 1

Packing dimensions (W x H x L): 0.31 x 0.23 x 0.32 m

Gross weight: 3.64 kg

Net weight: 2.73 kg

Item weight (w/o accessories): 2.7 kg