

## Tender text

### ESP-50AB/WS

#### PA A/B wall speaker,

with EN 54-24 certification for evacuation systems with A/B speaker distribution according to EN 60849 and DIN VDE 0833-4.

- 100 V line technique
- 2 separate full range speakers (10 cm), each with its own transformer 6/3/1.5 W
- Connection via 2 spring-loaded terminals inside the cabinet
- Wooden cabinet with protective metal grille
- Easy wall mounting via supplied metal bracket and mounting accessories
- Ball-proof according to DIN 18032, Part 3

#### Specifications:

|                                |                   |
|--------------------------------|-------------------|
| Active/passive                 | passive           |
| Transmission method            | 100 V             |
| Power rating (RMS)             | 2 x 6/3/1.5 W     |
| Frequency range                | 120-20,000 Hz     |
| Number of speakers             | 2                 |
| Speaker size                   | 10 cm             |
| Sensitivity                    | 92 dB/W/m         |
| Max. rated SPL                 | 99 dB             |
| Housing material               | wood              |
| Colour                         | white             |
| Mounting device                | metal bracket     |
| Protected against ball rebound | yes               |
| Admiss. ambient temp.          | -10 °C to +50 °C  |
| Dimensions                     | 265 x 165 x 90 mm |
| Width                          | 265 mm            |
| Height                         | 165 mm            |
| Depth                          | 90 mm             |
| Weight                         | 1.9 kg            |

Brand: MONACOR

Type: ESP-50AB/WS

Quantity: 1

Packing dimensions (W x H x L): 0.17 x 0.27 x 0.1 m

Gross weight: 2.12 kg

Net weight: 1.9 kg

Item weight (w/o accessories): 1.9 kg