

Tender text

ESP-8U

PA wall and ceiling speaker for flush mounting

- 100 V line technique via audio transformer with 3 power taps
- Perfect sound presence for a powerful voice reproduction with a very high audibility
- 20 cm speaker of very sensitivity (99 dB/W/m)
- Plastic tray for flush mounting in walls or solid ceilings
- Required hole in wall: approx. 242 x 242 x 100 mm
- Metal front grille with plastic frame

Specifications:

Transmission technology	100 V
Frequency range	200-17,000 Hz
Power rating (RMS)	6/3/1.5 W
SPL	99 dB/W/m
Mounting cutout	242 x 242 mm
Mounting depth	100 mm
Dimensions	248 x 248 x 100 mm
Width	248 mm
Height	248 mm
Depth	100 mm
Colour	white/black
Admiss. ambient temp.	0-40 °C
Weight	1.7 kg
Packing unit	1
Type of speaker	200
Packing dimensions (W x H x L)	0.255 x 0.115 x 0.255 m
Gross weight	1.86 kg
Net weight	1.69 kg

Brand: MONACOR

Type: ESP-8U

Quantity: 1

Packing dimensions (W x H x L): 0.255 x 0.115 x 0.255 m

Gross weight: 1.86 kg

Net weight: 1.69 kg

Item weight (w/o accessories): 1.7 kg