

## Tender text

### ETS-515TW/WS

#### PA column speaker

- 100 V line technique or 8  $\Omega$  operation
- 2-way version (with additional integrated tweeter for a clearly improved sound)
- Integrated crossover network
- 6-step power selector switch with 8  $\Omega$  switching
- 2 x 6 mm threaded bushing
- Plastic cabinet and protective metal grille in black (SW) or white (WS)
- Supplied with mounting bracket
- Connection via spring-loaded speaker terminal

#### Specifications:

Active/passive	passive
Transmission technology	100 V
Total power rating	30 W
Power rating (RMS)	15/7.5/4/2/1 W (100 V) 15 W (8 $\Omega$ )
Impedance	8 $\Omega$
Frequency range	90-20,000 Hz
System	2-way
Full range speaker	
Number of speakers	2+1
SPL	87 dB/W/m
Features	
Housing material	plastic
Colour	white
Mounting device	mounting brackets
Admiss. ambient temp.	0-40 °C
Dimensions	128 x 385 x 140 mm
Width	128 mm
Height	385 mm
Depth	140 mm
Weight	2.8 kg
Replacement voice coil	
Accessories	
Packing dimensions (W x H x L)	0.18 x 0.18 x 0.5 m
Gross weight	3.1 kg
Net weight	2.84 kg

Brand: MONACOR

Type: ETS-515TW/WS

Quantity: 1

Packing dimensions (W x H x L): 0.18 x 0.18 x 0.5 m

Gross weight: 3.1 kg

Net weight: 2.84 kg

Item weight (w/o accessories): 2.8 kg