Tender text

EUL-26/WS

Pairs of miniature PA speaker systems

• Speakers for general applications, very small dimensions in 100 V technology
• Can also be connected at 8 Ω
• 6.5 cm (2.5") full range speaker
• Good sound characteristics and speech intelligibility
• Turnable, movable and tiltable due to wall bracket with ball joint
• For completing the low-frequency sound reproduction, an additional subwoofer system is recommended (e.g. EUL-2SUB/SW, SOUND-100SUB)

Specifications:

Active/passive	passive
Transmission method	100 V
Total power rating	20 W
Power rating (RMS)	6 W (100 V) 10 W (8 Ω)
Impedance	8 Ω
Frequency range	150-20,000 Hz
Number of speakers	1
Speaker size	6.5 cm (2.5")
Sensitivity	88 dB/W/m
Colour	white
Mounting device	wall bracket
Admiss. ambient temp.	0-40 °C
Dimensions	90 x 90 x 115 mm
Width	90 mm
Height	90 mm
Depth	115 mm
Weight	0.65 kg
Inputs	spring-load. speaker term.
Other features	pair

Brand: MONACOR

Type: EUL-26/WS

Quantity: 2

Gross weight: 1.436 kg

Net weight: 1.306 kg

Item weight (w/o accessories): 0.65 kg