[Ausschreibung]

SP-302C

Car hi-fi subwoofer, 150 W, 4 Ω

• 30 cm (12") subwoofer
• Coated cone
• Also suitable as a bass addition for free air applications
• Protruding lower pole plate for an even longer excursion
• Low resonance up to midrange

[Technische Daten]:

Impedance (Z)	4 Ω
Frequency range	f3-3,000 Hz
Resonant frequency (fs)	33 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,000 Hz
Power rating	150 W
Peak music power output	300 W
Sensitivity	93 dB/W/m
Suspension compl. (Cms)	0.39 mm/N
Moving mass (Mms)	62 g
Mech. Q factor (Qms)	4.19
Electr. Q factor (Qes)	0.71
Total Q factor (Qts)	0.61
Equivalent volume (Vas)	155 l
DC resistance (Re)	3.7 Ω
Force factor (BxL)	7.99 Tm
Voice coil induct. (Le)	0.4 mH
Voice coil diameter	39 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	± 5 mm
Eff. cone area (Sd)	531 cm^2
Magnet weight	850 g
Magnet diameter	125 mm
Mounting cutout	Ø 282 mm
Mounting depth	130 mm
Dimensions	Ø 305 mm x 129 mm
Outside diameter	Ø 305 mm
Width	305 mm
Depth	129 mm
Admiss. ambient temp.	0-40 °C
Weight	2.535 kg
Sales unit	1
Type of speaker	12"

Brand:

Type:

Quantity: 1

Packing dimensions: