[Ausschreibung]

STA-1508

Multi-channel PA amplifiers,

with integrated limiter.

STA-1508 = 8 channels
STA-1506 = 6 channels
STA-1504 = 4 channels

• Balanced inputs
• High-pass filter, low-pass filter, can be activated as required for each channel
• Tamper-resistant level adjustment on the rear panel
• 8 Ω bridged operation possible
• LED VU meter and LED per channel for indicating overload (clip)
• Soft start
• Ground lift switch
• Speaker switch-on delay
• Fan cooling
• Protected against short circuit, overheating and DC voltage overlay at the outputs

[Technische Daten]:

Channels	8
Power rating	1,280 W
Power rating at 4 Ω	8 x 160 W
Power rating at 8 Ω	8 x 100 W
Power rating with 8 Ω bridged operation	4 x 320 W
Peak music power output (P_{MAX})	1,800 W
Inputs	0.7 V/20 kΩ
Attenuation factor	
Frequency range	12-20,000 Hz
Crossover network	yes
Crossover frequency	240 Hz
Integrated limiter	yes
S/N ratio	> 80 dB
Crosstalk attenuation	> 60 dB
THD	< 0.1%
Power supply	~ 230 V/50 Hz/2,400 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	2,400 VA
Admiss. ambient temp.	0-40 °C
Dimensions	482 x 132 x 310 mm, 3 RS
Width	482 mm
Height	132 mm
Depth	310 mm

Rack spaces, RS	3
Weight	16.7 kg
Connections	8 x 3-pole XLR, bal. 8 x screw terminal

Brand:

Type:

Quantity: 1

Packing dimensions: