[Ausschreibung]

PAB-82WP/WS

Weatherproof high-performance PA speaker system, 120 W

• High-performance 2-way coaxial speaker system in an ABS cabinet
• 100 V operation or 8 Ω operation, selectable
• 20 cm (8") PA coaxial system with impregnated paper cone
• Coaxially integrated 25 mm (1") horn tweeter
• Excellent sound characteristics
• Front grille with water-repellent gauze
• Recessed connection terminal with cover plate and high-strength cable gland
• SPEAKER in and parallel out, screw terminal
• Metal parts and wall bracket made of stainless steel
• Protected against ball rebound acc. to DIN 18032, part 3

[Technische Daten]:

Active/passive	passive
Line technique	100 V
Impedance	8 Ω
Frequency range	50-20,000 Hz
System	2-way coaxial
Bass speaker	20 cm (8") PA coaxial
Tweeter	25 mm (1") horn tweeter
Number of speakers	2
Speaker size	20 cm (8")
Power rating	120/60/30 W
Peak music power output	240 W
Sensitivity	96 dB/W/m
Max. rated SPL	117 dB
Features	
Material (housing/cabinet)	ABS
Colour	white
Mounting facility	mounting bracket
Protective class	IP45
Admiss. ambient temp.	-10-+40 °C
Width	280 mm
Height	280 mm
Depth	270 mm
Weight	9.5 kg
Inputs	1 x NEUTRIK SPEAKON, screw terminal
Outputs	1 x NEUTRIK SPEAKON, par. out
Replacement voice coil	

Brand:

Type:

Quantity: 1

Packing dimensions: