Tender text

HPB-1502

Car hi-fi amplifier, 2 channels, 500 W

• Due to the high power, a perfect 2-channel amplifier e.g. for complete rear-shelf systems or for subwoofers
• Adjustable low-pass filter and high-pass filter
• Can be bridged
• Bass boost
• Par. line out, mono/stereo selection
• High-power input possible with FGA-22 or FGA-22HQ

Specifications:

Peak output power	750 W
Power rating	500 W
Power rating at 2 Ω	2 x 250 W
Power rating at 4 Ω	2 x 175 W
Power rating with 4 Ω bridged operation	1 x 500 W
Channels	2
Inputs	0.4-4 V/20 kΩ
Attenuation factor	
Frequency range	20-2,000 Hz
Crossover frequency	40-300 Hz, 6 dB/oct. (low-pass filter)
	40-500 Hz, 6 dB/oct. (high-pass filter)
Crosstalk attenuation	> 50 dB
THD	< 0.2%
Operating voltage (possible alternative)	DC 12 V
Power supply (possible alternative)	45 A
Admiss. ambient temp.	0-40 °C
Width	252 mm
Height	62 mm
Depth	363 mm
Weight	2.985 kg
Connections	screw terminals (speakers) 1 x RCA L/R (line in) 1 x RCA L/R (line out)

Brand: MONACOR

Type: HPB-1502

Quantity: 1

Packing dimensions (W x H x L): 0.285 x 0.08 x 0.445 m

Gross weight: 3.675

Net weight: 2.985 kg

Item weight (w/o accessories): 2.985 kg