

Tender text

IMC-300T/EN

High-quality 2-way PA pendant speaker,

with 360° sound radiation.

- 100 V line technique: 30/20/10 W
- 2-way coaxial speaker (6.5")
- Elaborate reflector design for a wide and homogeneous omnidirectional radiation
- Excellent sound reproduction due to the attached housing, even down to the bass
- Recommended installation height: approx. 4 m (reflector)
- White lacquered sheet steel housing
- Device is suspended via steel safety ropes and snap hooks
- Cable inlet via high-strength cable gland (PG11)
- Ceramic terminal

Specifications:

Active/passive	passive
Transmission method	100 V
Power rating (RMS)	30/20/10 W
Frequency range	60-20,000 Hz
Bass speaker	1
Tweeter	1
Number of speakers	2
Speaker size	6.5"
Sensitivity	83 dB/W/m
Max. rated SPL	98 dB
Radiation angle, horizontal	360°
Radiation angle, vertical	160°
Housing material	metal
Colour	white
Mounting device	safety ropes with snap hook
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 480 mm x 300 mm
Width	Ø 480 mm
Height	300 mm
Weight	4.5 kg
Inputs	1 x high-strength cable gland (PG11)
Accessories	with safety rope for suspended installation

Type: IMC-300T/EN

Quantity: 1

Packing dimensions (W x H x L): 0.57 x 0.36 x 0.57 m

Gross weight: 7.66 kg

Net weight: 5 kg

Item weight (w/o accessories): 4.5 kg