

ECMS-60

Order No. 23.6950



Large diaphragm condenser microphone, for professional studio applications.

- Compact design
- 2.5 cm (1") extra thin gold-plated diaphragm
- 48 V phantom power
- Supplied with microphone holder with 16 mm ($\frac{5}{8}$ " thread and leather bag

| Model | ECMS-60 |
|-----------------------|------------------------------|
| Polar pattern | cardioid |
| System | FET condenser |
| Audio frequency range | 20-20,000 Hz |
| Nominal impedance | 200 Ω |
| Sensitivity | 17,8 mV/Pa |
| S/N ratio | > 70 dB |
| Max. sound pressure | 125 dB |
| Power supply | = 48 V, phantom power |
| Housing material | metal |
| Dimensions | \varnothing 50 mm x 130 mm |
| Weight | 290 g |
| Connection | XLR, bal. |



ECMS-50USB

Order No. 23.6940



Large diaphragm USB condenser microphone, for ambitious home recording.

- For operating directly at a PC or laptop
- No driver installation required, device will be identified automatically
- Integrated high-quality A/D converter: 48 kHz/16 bits
- 2.5 cm (1") extra thin gold-plated diaphragm
- Supplied with vibration absorbing support (spider) with 16 mm ($\frac{5}{8}$ " thread, 1.8 m USB connection cable and leather bag
- Suitable for Windows* 2000/XP/Vista/7/8/10 or Mac OS* X

| Model | ECMS-50USB |
|-----------------------|------------------------------|
| Polar pattern | cardioid |
| System | electret condenser |
| Audio frequency range | 20-18,000 Hz |
| Sensitivity | 25 mV/Pa |
| S/N ratio | > 78 dB |
| Max. sound pressure | 138 dB |
| Power supply | = 5 V via USB interface |
| Housing material | metal |
| Dimensions | \varnothing 50 mm x 185 mm |
| Weight | 250 g |
| Cable | 1.8 m |
| Connection | USB Type-B jack |

