

Components

Stage and Audio Accessories

DM-500USB

Order No. 23.5260



Dynamic microphone, with USB connector.

- For operating directly at a PC
- No driver installation required, device will be identified automatically
- Microphone cartridge with supercardioid polar pattern
- Integrated A/D converter
- Suitable for Windows* XP/Vista/7/8 or Mac OS* 9/X

| Model | DM-500USB |
|-----------------------|----------------------|
| Polar pattern | supercardioid |
| System | dynamic |
| Audio frequency range | 50-16,000 Hz |
| Nominal impedance | 600 Ω |
| Sensitivity | 2.5 mV/Pa |
| Max. sound pressure | 140 dB |
| Dimensions | Ø 50 mm x 210 mm |
| Weight | 208 g |
| Cable | 3 m, USB Type-A plug |
| Connection | fitted cable |



DM-70/SW

Order No. 23.1700

Dynamic microphone, for general PA applications.

- Cardioid polar pattern
- Plastic version
- On/off switch

| Model | DM-70/SW |
|-----------------------|-----------------------------|
| Polar pattern | cardioid |
| System | dynamic |
| Audio frequency range | 100-10,000 Hz |
| Nominal impedance | 600 Ω |
| Sensitivity | 1.4 mV/Pa |
| Dimensions | Ø 53 mm x 205 mm |
| Weight | 126 g |
| Cable | 3 m, low-noise, 6.3 mm plug |
| Connection | fitted cable |



ECM-700

Order No. 23.0360

Electret microphone, miniature version.

- Microphone cartridge with omnidirectional polar pattern
- Removable clip
- On/off switch
- 1 m cable with 3.5 mm plug

| Model | ECM-700 |
|-----------------------|------------------|
| Polar pattern | omnidir. |
| System | electret |
| Audio frequency range | 100-10,000 Hz |
| Nominal impedance | 2.2 kΩ |
| Sensitivity | 7.9 mV/Pa |
| S/N ratio | > 58 dB |
| Max. sound pressure | 110 dB |
| Power supply | ≈ 1-10 V |
| Dimensions | Ø 17 mm x 120 mm |
| Weight | 21 g |
| Cable | 1 m |
| Connection | 3.5 mm plug |



ECM-10/SW

Order No. 23.2720

ECM-10/WS

Order No. 23.2730

Built-in electret microphones

- Particularly suitable for PA applications
- Metal housing
- Black (SW) or white (WS) cartridge cover

| Model | ECM-10/SW, ECM-10/WS |
|-----------------------|-------------------------|
| Polar pattern | omnidir. |
| System | electret |
| Audio frequency range | 30-17,000 Hz |
| Nominal impedance | 300 Ω |
| Sensitivity | 2.3 mV/Pa |
| Max. sound pressure | 110 dB |
| Power supply | ≈ 9-48 V, phantom power |
| Dimensions | Ø 30 mm x 71 mm |
| Weight | 92 g |
| Connection | XRL, bal. |



DH-95N

Order No. 23.0030

DH-95NP

Order No. 23.4100

Hand-held dynamic microphones

- Low impedance
- With push-to-talk button
- Particularly suitable for CB and PA
- Supplied with microphone holder
- 300-6,000 Hz, 2.5 mV/Pa/1 kHz, 500 Ω



DH-95N: helix connection cable with bare cable ends

DH-95NP: helix connection cable with 6.3 mm stereo plug

MH-95

Order No. 23.0920

Push-to-talk microphone holder, screw-mounted.

