Stage and Audio Accessories

MD-306

Order No. 22.1070

Stereo headphones

- Extra lightweight version
- Turnable earpieces
- Padded ear cushions
- 1.2 m cable with single-sided cable inlet and 3.5 mm plug

MD-306
neodymium, Ø 30 mm
dynamic
50 mW
20-20,000 Hz
32 Ω
110 dB/mW
1.2 m, single-sided cable inlet
3.5 mm plug
50 g



MD-302

Order No. 22.1160

Stereo headphones

- Extra lightweight version
- Turnable earpieces
- 1.2 m cable with single-sided cable inlet and 3.5 mm plug

Model	MD-302
Headphone driver	neodymium, Ø 30 mm
Type of transducer	dynamic
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	110 dB/mW
Cable	1.2 m, single-sided cable inlet
Plug	3.5 mm plug, nickel-plated
Weight w/o cable	50 g



MD-260

Order No. 22.0760

Stereo headphones

- Comfortable and secure fit due to earband/neckband
- Removable foam ear cushions
- Single-sided cable inlet
- 1.5 m connection cable with a 3.5 mm stereo plug

Model	MD-260
Headphone driver	Ø 30 mm
Type of transducer	dynamic
Max. input power	80 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	101 dB/mW
Cable	1.5 m, single-sided cable inlet
Plug	3.5 mm plug, stereo
Weight w/o cable	35 g
weight w/o cable	30 g



MD-39

Order No. 22.0070

Stereo headphones

- Well-balanced sound
- Universal headphones
- Extra lightweight version
- 1.2 m cable with 3.5 mm stereo plug

Model	MD-39
Headphone driver	ferrite
Type of transducer	dynamic
Max. input power	100 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Cable	1.1 m
Plug	3.5 mm plug
Weight w/o cable	28 g



MD-22

Order No. 22.1270

Stereo headphones

- Ideally suited for guided tours, coaches, hospitals or hotels
- 1.5 m cable with 3.5 mm stereo plug
- Individually packed in a plastic bag

Model	MD-22
Headphone driver	ferrite, Ø 27 mm
Max. input power	20 mW
Cable	1.5 m
Plug	3.5 mm plug
Weight w/o cable	25 g

