

SE-30

Order No. 22.0110

In-ear stereo earphones

- Universal monitoring earphones
- Silicone earpieces, comfortable to wear
- 3.5 mm stereo plug

Model	SE-30
Headphone driver	Ø 10 mm
Type of transducer	dynamic
Max. input power	50 mW
Transmission range, headphones	100-18,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	90 dB/mW
Cable	1.2 m
Plug	3.5 mm stereo plug
Weight w/o cable	4 g



SE-20

Order No. 22.0700

Stereo earphones

- Ideal for guided tours, coaches, hospitals or hotels
- Replaceable foam cushions
- 3.5 mm stereo plug
- Individually packed in a plastic bag

Model	SE-20
Type of transducer	dynamic
Max. input power	20 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	98 dB/mW
Cable	1.2 m
Plug	3.5 mm stereo plug
Weight w/o cable	3 g



SE-80

Order No. 22.0330

In-ear stereo earphones

- Excellent sound with a powerful bass reproduction and a brilliant reproduction of the high frequencies
- Silicone sleeves, comfortable to wear, including 1 pair of replacement sleeves
- 3.5 mm stereo plug

Model	SE-80
Headphone driver	neodymium, Ø 10 mm
Type of transducer	dynamic
Max. input power	15 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	103 dB/mW
Cable	1.2 m
Plug	3.5 mm stereo plug
Weight w/o cable	4 g



SE-62

Order No. 22.0940

In-ear stereo earphones

- Well-balanced and clear sound with a full bass reproduction
- Supplied with 2 pairs of sleeves in different shapes
- Storage bag
- Gold-plated 3.5 mm stereo plug

Model	SE-62
Headphone driver	Ø 10 mm
Type of transducer	dynamic
Max. input power	50 mW
Transmission range, headphones	10-20,000 Hz
Nominal impedance, headphones	16 Ω
Headphone sensitivity	103 dB/mW
Cable	1 m
Plug	3.5 mm stereo plug
Weight w/o cable	4 g



SE-52

Order No. 22.0060

Stereo earphones

- Optimised for mobile audio devices
- Well-balanced sound
- 3.5 mm stereo plug

Model	SE-52
Headphone driver	Ø 10 mm
Type of transducer	dynamic
Max. input power	30 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	108 dB/mW
Cable	1.2 m
Plug	3.5 mm stereo plug
Weight w/o cable	6 g



SE-50

Order No. 22.0710

Stereo earphones

- Well-balanced sound
- 3.5 mm stereo plug

Model	SE-50
Type of transducer	dynamic
Max. input power	20 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	98 dB/mW
Cable	1.2 m
Plug	3.5 mm stereo plug
Weight w/o cable	3 g

