

Components

Stage and Audio Accessories

NTA-2SE

Order No. 23.5210

Adapter

3.5 mm stereo plug to 2.5 mm stereo inline jack.

For connecting headband and earband microphones HSE-70A/SK, HSE-150A/SK and HSE-152A/SK.



NTA-3A

Order No. 23.5220

Adapter

3-pole mini XLR inline jack to 2.5 mm stereo inline jack.

For connecting headband and earband microphones HSE-70A/SK, HSE-150A/SK and HSE-152A/SK.



NTA-4SH

Order No. 23.5240

Adapter

4-pole mini XLR inline jack to 2.5 mm stereo inline jack.

For connecting headband and earband microphones HSE-70A/SK, HSE-150A/SK and HSE-152A/SK.



NTA-4M

Order No. 23.5230

Adapter

4-pole mini XLR inline jack to 2.5 mm stereo inline jack.

For connecting headband and earband microphones HSE-70A/SK, HSE-150A/SK and HSE-152A/SK.



NTA-4AT

Order No. 23.6570

Adapter

4-pole Hirose inline jack to 2.5 mm inline jack.

For connecting headband or earband microphones with 2.5 mm plug to wireless transmission systems of other manufacturers.



HSE-70C

Order No. 23.5200

Replacement connection cable

- Suitable for earband microphones HSE-70A/SK, HSE-150A/SK, HSE-152A/SK
- Beige version
- Length: 1.2 m



MH-2/SK

Order No. 23.5770

MH-2/SW

Order No. 23.5780

Clips

- For connection cables of headband or earband microphones
- Beige (/SK) or black (/SW) lacquered metal version
- For cables up to: Ø 1.5 mm



EP-302

Order No. 22.1170

4x

Foam headphone pads, 4 pcs., black, for MD-302 or similar headphones.

Dimensions of opening:
normal: 39 x 48 mm, max.: 56 x 62 mm.



EP-4

Order No. 22.0220

4x

Set of foam headphone pads, 2 blue pads, 2 black pads, for MD-39 or similar-sized headphones.

Dimensions of opening:
normal: Ø 18 mm, max.: Ø 35 mm.



EP-6/SW

Order No. 22.1150

6x

Foam earphone pads, 6 pcs., black, for SE-50, SE-20 or similar earphones.

Dimensions of opening:
normal: Ø 7.5 mm, max.: Ø 15 mm.



PB-05E

Order No. 25.5680

Automatic microphone switch, with optical distance sensor.

- For dynamic microphones with balanced output configuration
- Operation via 48 V phantom power
- Adjustable distance: 0-1.5 m, detection angle: 15°

