

# Components

## Energy, Measuring and DIY

### PSS-600E

Order No. 27.3030



#### Switch-mode power supply, 0.6 A,

high energy efficiency, complies with EU ecodesign directive.

- Saves electricity costs due to low power consumption in standby mode (< 0.3 W)
- Switchable output voltage
- Protected against short circuit, overload and overheating
- Power LED
- 1.8 m connection cable
- Selectable polarity by reversing the supplied adapters

Model	PSS-600E
Input voltage	~ 100-240 V/50-60 Hz/160 mA
Output voltage	= 3/4.5/5/6/7.5/9/12 V
Charging/output current	600 mA
Admiss. ambient temp.	0-40 °C
Dimensions	38 x 50 x 68 mm
Weight	99 g

- 7 plug-in adapters: plugs: 2.5 mm, 3.5 mm, hollow plugs: 2.35/0.75 mm, 3.5/1.35 mm, 5.0/2.1 mm, 5.5/2.1 mm, 5.5/2.5 mm



### PSS-1000E

Order No. 27.3130



### PSS-1000USB

Order No. 27.3330



#### Switch-mode power supplies, 1 A, with high

energy efficiency, complies with EU ecodesign directive.

- Saves electricity costs due to low power consumption in standby mode (< 0.3 W)
- Switchable output voltage
- Protected against short circuit, overload and overheating
- Power LED
- 1.8 m connection cable
- Selectable polarity by reversing the supplied adapters

Model	PSS-1000E	PSS-1000USB
Input voltage	~ 100-240 V/50-60 Hz/ 250 mA	~ 100-240 V/50-60 Hz/ 250 mA
Output voltage	= 3/4.5/5/6/7.5/9/12 V	= 3/4.5/5/6/7.5/9/12 V
Charg./output current	1 A	1 A
Admiss. ambient temp.	0-40 °C	0-40 °C
Dimensions	43 x 52 x 76 mm	43 x 53 x 76 mm
Weight	135 g	149 g

- 7 plug-in adapters: plugs: 2.5 mm, 2.5 mm, hollow plugs: 2.35/0.75 mm, 3.5/1.35 mm, 5.0/2.1 mm, 5.5/2.1 mm, 5.5/2.5 mm

**PSS-1000USB:** additionally with USB Type-A inline jack



PSS-1000USB



### PSS-1500E

Order No. 27.3140



#### Switch-mode power supply, 1.5 A,

high energy efficiency, complies with EU ecodesign directive.

- Saves electricity costs due to low power consumption in standby mode (< 0.3 W)
- Switchable output voltage
- Protected against short circuit, overload and overheating
- Power LED
- 1.8 m connection cable
- Selectable polarity by reversing the supplied adapters

Model	PSS-1500E
Input voltage	~ 100-240 V/50-60 Hz/350 mA
Output voltage	= 3/4.5/5/6/7.5/9/12 V
Charging/output current	1.5 A
Admiss. ambient temp.	0-40 °C
Dimensions	52 x 54 x 82 mm
Weight	160 g

- 7 plug-in adapters: plugs: 2.5 mm, 3.5 mm, hollow plugs: 2.35/0.75 mm, 3.5/1.35 mm, 5.0/2.1 mm, 5.5/2.1 mm, 5.5/2.5 mm



### PSS-1500SV

Order No. 27.3450



#### Switch-mode power supply, 1.5 A,

high energy efficiency, complies with EU ecodesign directive.

- Saves electricity costs due to low power consumption in standby mode (< 0.3 W)
- Switchable output voltage
- Protected against short circuit, overload and overheating
- Power LED
- 1.8 m connection cable
- Selectable polarity by reversing the supplied adapters

Model	PSS-1500SV
Input voltage	~ 100-240 V/50-60 Hz/500 mA
Output voltage	= 9/12/13.5/15/18/20/24 V
Charging/output current	1.5 A (9-15 V) 1.2 A (18-20 V) 1 A (24 V)
Admiss. ambient temp.	0-40 °C
Dimensions	52 x 59 x 95 mm
Weight	226 g

- 7 plug-in adapters: plugs: 2.5 mm, 3.5 mm, hollow plugs: 2.35/0.75 mm, 3.5/1.35 mm, 5.0/2.1 mm, 5.5/2.1 mm, 5.5/2.5 mm

