

Components

Stage and Audio Accessories

ES-200

Order No. 22.0130

Mono earphone

- Plastic holder and ear cartridge, adjustable in height for an optimum fit
- Dynamic 32 Ω system
- 1 m connection cable and 3.5 mm mono plug

Model	ES-200
Headphone driver	ferrite
Type of transducer	dynamic
Max. input power	100 mW
Transmission range, headphones	100-18,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	100 dB/mW
Cable	1 m
Plug	3.5 mm mono plug
Weight w/o cable	22 g



ES-10

Order No. 22.0590

Mono earphone

- Plastic holder for an optimum fit
- Dynamic 32 Ω system
- 1 m connection cable and 3.5 mm mono plug

Model	ES-10
Headphone driver	mylar, \varnothing 15 mm
Type of transducer	dynamic
Max. input power	30 mW
Transmission range, headphones	30-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	110 dB/mW
Cable	1 m
Plug	3.5 mm mono plug
Weight w/o cable	11 g



ES-16

Order No. 22.0740

Mono earphone

- Flexible rubber ear hook for a secure fit
- Dynamic 32 Ω system
- 1.2 m connection cable with gold-plated 3.5 mm stereo plug

Model	ES-16
Type of transducer	dynamic
Max. input power	50 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	105 dB/mW
Cable	1.2 m
Plug	3.5 mm stereo plug
Weight w/o cable	8 g



ES-220

Order No. 22.0190

Mono earphone

- Approved ring holder for a tight fit
- Magnetic 8 Ω system
- 1.5 m connection cable and 3.5 mm mono plug

Model	ES-220
Headphone driver	ferrite
Type of transducer	dynamic
Max. input power	100 mW
Transmission range, headphones	100-18,000 Hz
Nominal impedance, headphones	8 Ω
Headphone sensitivity	125 dB/mW
Cable	1.5 m
Plug	3.5 mm mono plug
Weight w/o cable	22 g



ES-230

Order No. 22.0250

Mono earphone, lightweight version.

- Flexible soft ring holder for a comfortable fit
- Magnetic 8 Ω system
- 1.5 m connection cable and 3.5 mm mono plug

Model	ES-230
Headphone driver	neodymium, \varnothing 23 mm
Type of transducer	dynamic
Max. input power	40 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	8 Ω
Headphone sensitivity	110 dB/mW
Cable	1.5 m
Plug	3.5 mm mono plug
Weight w/o cable	20 g



S-83

Order No. 22.0140

Earphone

- Magnetic system
- With connection lead and 3.5 mm plug

